

## GOLF GRIP DOUBLE-FACED CREPE PAPER TAPE

### TYPICAL APPLICATIONS

- Factory and clubhouse golf grip installation
- Mounting, holding, splicing, tabbing and fastening of a variety of other substrates that need an aggressive, double-faced tape
- Grip side adhesive – specially formulated for effective grip installation
- Shaft side adhesive – designed for superior adhesion to graphite, steel and titanium
- When used as a golf grip installation tape, offers fast set-up and easy clean up
- Good tensile strength
- Both tape and release liner are wrinkle-resistant

### CONSTRUCTION

Overall Grade/Function: Golf Grip Installation  
Backing: Crepe paper  
Adhesive: Rubber-based  
Liner: Siliconized, crepe paper release liner



### COLOR(S)

 Natural (NAT)

### STANDARD WIDTH(S)

12 mm    18 mm    24 mm    48 mm

### STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	6.6 mils	0.17 mm
Elongation	10%	10%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.