

SMALL ENGINE OIL CHANGE KIT

INSTRUCTIONS:

1. Start your mower or small engine and allow it to warm up. After approx. 5 minutes turn the engine off.

▲CAUTION: *Oil and motor may be hot.*

2. Put down newspaper or shop towels to catch any oil that may spill or drip.
3. Position the mower or small engine on the newspaper and stabilize so it won't tip or roll.
4. Connect the flexible hose to the syringe by inserting the end into the nipple at the front of the syringe.
5. Remove the dipstick/plug and insert the flexible syringe hose. Be sure to insert as far as it will go.
6. Slowly pull the center handle of the syringe to draw the oil in. Continue until full.
7. Remove the flexible hose from the dipstick or plug hole. Insert the end into the waste oil storage container and push the syringe's plunger back in.
8. Repeat steps 4-6 until all the oil has been removed. It may take a few times depending on capacity.
9. Use the supplied funnel to fill engine with new engine oil. Refer to the owner's manual for the type and amount of oil required.
10. Wait a few minutes and check the oil level with the dipstick. Engines without a dipstick get filled to the base of the plug port. Refer to the owner's manual for that procedure.
11. Replace dipstick or plug and tighten firmly.
12. Clean the area and dispose of used oil and newspaper per your city's recommended oil disposal.

