



RUGGED GO FOR AUTOMATIC EXTERNAL DEFIBRILLATORS (AED)

SOLUTION FOR AED MONITORING

The CARDIACT GO allows the remote monitoring of the AED. It provides information concerning any incident, event or malfunction through an AED Software management platform and a wireless communication via 4G so as to ensure the unit remains fully operational and present when required.

CARDIACT GO makes it easier to maintain your AED and provides helpful features for lay responders to be in direct communication emergency services via an integrated hands free phone.

SOFTWARE MONITORING APPLICATION

Accessible through secure access, from any computer connected to the Internet, the CARDIACT CONNECT server offers constant, remote monitoring of AEDs and their protective cabinets, providing users with realtime information concerning any incidents, alerts or malfunctions which may occur.

The following features and benefits of the CARDIACT CONNECT server are:

- 24/7 Access via Internet Portal
- User and password-protected access
- Colour code alert display
- Geolocalisation
- Events record (traceability)
- Email & Text Message Alerts (Incidents, Faults etc.)
- Statistical data recovery (extraction to Excel)

ADDITIONAL BENEFITS

- GPS tracking when moving with SMS
- Emergency calling button telephone communication*
- 3 visible LEDS report different functions
- SIM Card integrated for a wireless data and voice communications over 4G network



- ☐ **AED STATUS MONITORING**
- ☎ **EMERGENCY PHONE CALLS***
- 📍 **GPS TRACKING**

STANDARD FEATURES

- Constant remote monitoring of the AED (status, presence, surrounding, temperatures) through an optical sensor specific to brand and model
- Information concerning incidents, alerts or malfunctions
- Immediate and automatic routing of data via SMS/Email
- Communications via 4G for software management
- Battery-operated, 1 Lithium Battery Type C 3.6V 5.5Ah, with up to a 24 months autonomy



FEATURES & BENEFITS



Access

Monitors opening of case, will provide immediate text-message alerts if the case is opened



Tracking

GPS tracking of device when moved



Call Button

Automatically calls a predetermined number to alert responders. Two-way conversation can be made



Readiness

Monitors AED status and will alert stakeholders as to any issues that may arise



Versatile

Can be used with any brand of AED



Protected

IP67 Waterproof Case for added protection

Measurements
Weight (including AED)
Material (exterior)
Weather resistance
Power Source

330 x 280 x 120mm
2.8kg
Ultra-High-Impact Structural Polymer
IP67
Internal Batteries