



MP1045SW SURGE PROTECTOR AND USB COMBO PACK

Offering home/office environments with computer and communication grade surge protection.



SPECIFICATIONS

	P600WSURC1	P604U
PHYSICAL		
Dimensions (LxWxH) (in.)	2.2 x 4.1 x 5.7	2.74 x 2.19 x 12.2
Weight (lbs.)	0.6	1.014
Package Size (LxWxH) (in.)	3.03 x 9.8 x 15.5	
Package Weight (lbs.)	2.017	
SAFETY STANDARDS		
UL/cUL/CSA/NOM	cUL	cUL
POWER CORD		
Length (Exposed ft.)	Wall Tap	4' Standard
Plug Type	Three Prong Direct Plug-in	Right Angle 45°, 14AWG 60 70P
ENCLOSURE		
Color	Black	Black
Keyhole Slots	No	Yes
OUTLETS		
Total	6	6
Standard	6	6
CIRCUIT BREAKER		
15A Breaker/Switch	No	Yes

	P600WSURC1	P604U
SURGE PROTECTION AND FILTERING		
20D201 Mov 300J	4	3
Joules -	1200	900
Clamping Voltage	LN 400V	LN 400V
Maximum Peak Current	60000	45000
AC Lines Protected L-N	30000	15000
L-G	15000	15000
N-G	15000	15000
EMI/RFI	Yes	Yes
Attenuation	up to 32 db	up to 32 db
Unlighted Circuit Breaker	No	Yes, Black base Red cover
Automatic Shutdown	Yes	Yes
LED INDICATOR		
Grounded	YES	No
Protected	YES	YES
WARRANTY		
Connected Equipment	\$75,000	\$50,000
Product	limited lifetime	limited lifetime