

CyberPower

CSP6WSUC WALL-TAP SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower CSP6WSUC Wall-Tap Surge Protector with USB charging is designed to protect essential home and office electronics, including computers, networking equipment and other devices from power surges and energy spikes caused by storms and electrical fluctuations. Offering 2,400 joules of surge protection, this unit features six surge-protected AC outlets, a USB-A port with 2.4A power output, and a USB-C port delivering 15W of power, ensuring efficient charging for mobile and USB-enabled devices.

This surge protector wall-tap comes with a One Year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 2400 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 15W
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000



SPECIFICATIONS

INPUT		OUTPUT	
Cord Length	Wall-tap	Outlet Type	6 x NEMA 5-15R
Input Plug Type	NEMA 5-15P	Outlets - Total	6
Maximum Input Current	15 A	USB Charge Port Amperage COMPUTED	2.4 Amps (Shared)
Plug Style	Wall-tap	USB Charge Port Quantity	2
		USB Charge Port Type	1 Type A / 1 Type C
		USB Charge Port Voltage	5 VDC
		USB Charge Port Watts	18 Watts

CSP6WSUC

WALL-TAP SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING		PHYSICAL DIMENSIONS	
Attenuation	32 dB	Physical Dimensions - Width/Height/Depth (cm)	10.39 x 17.6 x 3.51 cm
Clamping Voltage	800V (H-N, H-G, N-G)	Physical Dimensions - Width/Height/Depth (mm)	104 x 176 x 35 mm
EMI/RFI Filtration	150 KHz / 100 MHz	Physical Dimensions - Width/Height/Depth (in.)	4.09 x 6.93 x 1.38 in.
Maximum Surge Current	60,000 A	Weight (kg)	0.29 kg
Maximum Surge Current H-G	15,000 A	Weight (lb)	0.64 lbs.
Maximum Surge Current H-N	30,000 A	SHIPPING DIMENSIONS	
Maximum Surge Current N-G	15,000 A	Shipping Dimensions - Width/Height/Depth (cm)	12.29 x 18.49 x 6.81 cm
Maximum Surge Voltage	6000	Shipping Dimensions - Width/Height/Depth (mm)	122.94 x 184.91 x 68.07 mm
Surge Suppression (Joules)	2400 J	Shipping Dimensions - Width/Height/Depth (in.)	4.84 x 7.28 x 2.68 in.
PHYSICAL		Weight (kg)	0.36 kg
Color	White	Weight (lb)	0.80 lbs.
Form Factor	Wall-tap	CERTIFICATIONS	
Form Factors Supported	Direct Plug	Environmental	RoHS Compliant
Material of Construction	Plastic	Safety	cULus (UL498A/UL1449) DOE VI NR Can FCC ICES-003
WARRANTY			
CEG Amount	\$300,000		
Connected Equipment Guarantee	Lifetime		
Product Warranty	1-Year Lifetime Warranty		