



**Materials:**

- Screws conform to SAE J429 GR 2 (exceeds ASTM A307).

**Finishes:**

- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Piece (lbs)
HRMS 025050	1/4"	1/2"	EG	0.01
HRMS 025075	1/4"	3/4"	EG	0.012
HRMS 025100	1/4"	1"	EG	0.015
HRMS 031100	5/16"	1"	EG	0.026
HRMS 031125	5/16"	1-1/4"	EG	0.03
HRMS 037100	3/8"	1"	EG	0.041
HRMS 037125	3/8"	1-1/4"	EG	0.047
HRMS 037150	3/8"	1-1/2"	EG	0.053

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

<b>Project:</b>	<input style="width: 90%;" type="text"/>		
<b>Architect / Engineer:</b>	<input style="width: 90%;" type="text"/>		
<b>Date:</b>	<input style="width: 15%;" type="text"/>	<b>Phone:</b>	<input style="width: 25%;" type="text"/>
<b>Contractor:</b>	<input style="width: 90%;" type="text"/>		
<b>Address:</b>	<input style="width: 90%;" type="text"/>		
<b>Notes:</b>	<input style="width: 90%;" type="text"/>		

**Approval Stamp:**