

3M Science.
Applied to Life.™



Quality without compromise.

3M™ Fire Barrier Watertight Spray

Get the job done right with a versatile spray that seals construction joints formed by exterior walls and floor/ceiling assemblies. Created by 3M scientists, this formula helps prevent washout at the slab edge and is designed to meet the harsh rigors of the ASTM D 6904 Rain Resistance, ASTM E 2307 Perimeter Joint and ASTM E 1966 Construction Joint fire tests — so you can face inspections with confidence.

Performs up to your standards.

3M™ Fire Barrier Watertight Spray is a sprayable, moisture-curing, hybrid siliconized polymer that forms a tough, elastomeric coating — ideal for firestopping areas that also require a watertight seal. When installed properly, it acts as a barrier to water while helping to control the transmission of fire, heat and smoke.



- ▶ Up to 3-hour fire protection in construction joints (ASTM E 1966 / UL 2079) and perimeter joints (ASTM E 2307)
- ▶ Elastic material maintains performance with up to ± 10% movement capabilities
- ▶ Helps minimize sound transfer — STC rating of 56 when tested in STC 56 rated wall assembly
- ▶ Paintable with primer
- ▶ Broad range of applications with an extensive portfolio of tested and listed systems
- ▶ Applied with conventional airless spray equipment
- ▶ Consistent results — robust formula is freeze/thaw resistant and seals uniformly in hot or cold conditions

3M™ Fire Barrier Watertight Spray

UPC	Product Number	Color	Unit/Volume	Pail Weight	Coverage*	Pallet Quantity
00076308982324	98-0441-1004-1	Red	5 gallon (18.9 liter)	65 lbs.	16 sq. ft./gal. (0.40 sq. m/liter)	24 pails
00076308861131	98-0441-1019-9	White				

*Calculated based on 1/10 in. (2.5mm) thick wet coating.

See the standard at [3M.com/Firestop](https://www.3m.com/Firestop).

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144

Phone 1-800-328-1687
Web [3M.com/Firestop](https://www.3m.com/Firestop)

© 3M 2017. All rights reserved. 3M is a trademark of 3M. Printed in U.S.A. 78-9236-7297-2