

CyberPower

P6WUCL

WALL-TAP SURGE PROTECTOR

Wall-tap surge protector with USB charging

The CyberPower P6WUCL Wall-tap Surge Protector with USB charging safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 900 joules of protection, has 6 surge-protected AC outlets, two USB-A ports with 2.4 Amps shared power output and one USB-C port rated at 18W PD to charge mobile, USB enabled devices. The CyberPower P6WUCL features a photo sensor activated light and an impact-resistant casing.

This surge protector wall-tap comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB-A charge ports: 2
- USB-A charge output: 2.4A (shared)
- USB-C charge ports: 1
- USB-C charge output: 18W PD
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100,000



SPECIFICATIONS

INPUT		OUTPUT	
Cord Length	Wall-tap	Outlet Type	6 x NEMA 5-15R
Input Plug Type	NEMA 5-15P	Outlets - Total	6
Maximum Input Current	15A	USB Charge Port Amperage	2.4 A (shared)
		USB Charge Ports	1 x USB-C 2 x USB-A
		USB Charge Port Voltage	5 VDC
		USB Charge Port Watts	18 Watts

P6WUCL

SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz
Maximum Surge Current	24,000 A
Maximum Surge Current H-G	8000 A
Maximum Surge Current H-N	8000 A
Maximum Surge Current N-G	8000 A
Maximum Surge Voltage	6000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	900 J
PHYSICAL	
Color	White
Form Factor Supported	Direct Plug
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	8.89 x 15.88 x 5.72 cm
Physical Dimensions - Width/Height/Depth (mm)	89 x 159 x 57 mm
Physical Dimensions - Width/Height/Depth (in.)	3.5 x 6.25 x 2.25 in.
Weight (kg)	0.33 kg
Weight (lb)	0.72 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	9.5 x 15.8 x 7.01 cm
Shipping Dimensions - Width/Height/Depth (mm)	95.0 x 157.99 x 70.1 mm
Shipping Dimensions - Width/Height/Depth (in)	3.74 x 6.22 x 2.76 in.
Shipping Weight (kg)	0.36 kg
Shipping Weight (lbs.)	0.80 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498A UL1449 4th Edition FCC PART 15B DOE VI
WARRANTY	
CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited