



P806UC SURGE PROTECTOR

Protect home and office computers and electronics

The CyberPower P806UC Surge Protector prevents spikes in energy caused by storms and electrical power surges from reaching your home electronics such as audio/video equipment, laptops and desktop computers, household appliances and small electronics. The P806UC provides 2700 joules of surge protection, 8 AC outlets, 1 USB-C charging port, one USB-A charging port, and a 6 foot braided power cord with a right-angle plug.

Features of the P806UC include automatic shutdown, an EMI/RFI noise filter, metal oxide varistor (MOV) technology, an On/Off switch with integrated 15-Amp circuit breaker, LED indicators, low profile plug, keyhole mounting slots, and damage-resistant construction. This surge protector comes with a Limited Lifetime Warranty and a \$300,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Consumer Electronics
- Personal Computers
- Phone/Fax/Modem
- Printers
- Stereos



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15R
OUTPUT	
Outlet Type	NEMA 5-15R
Outlets - Total	8
Outlets - Widely Spaced	4
USB-A Charge Port	Yes
USB-A Amperage	2.4 A (Shared)
USB-C Charge Port	Yes
USB-C Wattage	15W
USB Voltage	5V (#1)

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz, 100 MHzs
Maximum Surge Current	75,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	15,000 A
Response Time	< 1 nanosecond
Surge Suppression	2,700 J
MANAGEMENT & COMMUNICATIONS	
LED Indicators	Protected (green) Grounded (green)

P806UC

SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Cord Management	No
Form Factor	Strip
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	No
Dimensions (WxHxL) (in.)	3.86 x 1.73 x 11.02

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363 UL1449 UL1310 cUL
WARRANTY	
CEG Amount	\$300,000
Product Warranty	Limited Lifetime Warranty