



HT1208TC | HOME THEATER SURGE PROTECTORS

Protect home theater equipment, home and office computers, and other electronics

The Home Theater Surge Protector HT1208TC from CyberPower provides 3,150 joules of protection and 12 outlets (8 standard and 4 widely-spaced) to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. The HT1208TC also has coaxial line surge protection (cable/satellite/modem) and RG6 gold-plated connectors.

Features of the HT1208TC include automatic shutdown, a power cord (8 ft.), LED status indicators (Grounded, Protected), keyhole mounting slots, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a \$350,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 3,150 J
- Volts: 125 V
- Circuit breaker: 15 A
- Outlets: 12 surge-protected (8 standard + 4 widely-spaced)
- Power cord: 8 ft.
- Data line protection: Telephone, Coaxial
- LED indicators: Yes
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$350,000



SPECIFICATIONS

INPUT		OUTPUT	
Circuit Breaker	15 A	Outlet Type	12 NEMA 5-15R
Cord Length	8 ft (2.4 m)	Outlets - Total	12
Input Plug Type	NEMA 5-15P	USB Charge Port	No
Maximum Input Current	15 A	USB Charge Port Amperage	None
Plug Style	Right Angle - 45° Offset		
Switch	Yes		

HT1208TC

HOME THEATER SURGE PROTECTORS

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	1 in 1 out
EMI/RFI Filtration	Yes
Maximum Surge Current	150,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	90,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Network Protection RJ45	1-in / 2-out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	3,150 J

PHYSICAL

Color	Black
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic

DIMENSIONS

Physical Dimensions - WxHxD (cm)	10.01 x 3.66 x 29.11 cm
Physical Dimensions - WxHxD (mm)	100 x 37 x 291 mm
Physical Dimensions - WxHxD (in.)	3.94 x 1.44 x 11.46 in.
Weight (kg)	0.83 kg
Weight (lb)	1.82 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	39.37 x 4.37 x 16.76 cm
Shipping Dimensions - WxHxD (mm)	393.7 x 43.69 x 167.64 mm
Shipping Dimensions - WxHxD (in)	15.5 x 1.72 x 6.6 in.
Shipping Weight (kg)	0.86 kg
Shipping Weight (lbs.)	1.90 lbs.

CERTIFICATIONS

Safety	UL1449 3rd Edition cUL
--------	---------------------------

WARRANTY

CEG Amount	\$350,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime