

SPECIALTY GRADE, FLUORESCENT CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For general use, including color-coding, labeling, floor marking and book-binding
- Also used for stage preparation in the motion picture and audio/visual industries
- Can also be used for a variety of applications in the hospitality, motorsports and floral industries

PRODUCT FEATURES

- Indoor use
- Conformable
- Easy to unwind and tear
- Available in a variety of fluorescent colors

CONSTRUCTION

Overall Grade/Function: Specialty

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



FLUORESCENT GREEN
(FLG)



FLUORESCENT PINK
(FLP)



FLUORESCENT ORANGE
(FLO)



FLUORESCENT YELLOW
(FLY)

PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 22 lbs/in width | 38.5 N/10 mm |
| Adhesion to Stainless Steel | 50 oz/in width | 5.47 N/10 mm |
| Thickness | 9 mils | 0.23 mm |
| Elongation | 16% | 16% |
| Service Temperature Range | 40 F to 200 F | 4 C to 93 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

