

# P-68

**Shurtape®**  
TRUE TO YOUR WORK™

## PREMIUM GRADE, HEAVY DUTY GAFFER'S TAPE

### TYPICAL APPLICATIONS

- For book-binding, color-coding and gaffer's applications
- For sealing containers and rooms, abrasion protection, and general holding, bundling and repair applications

### PRODUCT FEATURES

- High tensile strength
- Abrasion-resistant
- Conformable
- Hand-tearable in machine and cross directions

### CONSTRUCTION

Overall Grade/Function: Premium  
Backing: Matte-finish coated cloth  
Adhesive: Synthetic rubber

### STANDARD WIDTH(S)

2 in      3 in

### STANDARD LENGTH(S)

60 yd

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

CID A-A-1586A

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



**BLACK**  
(BLK)



**WHITE**  
(WHI)

PHYSICAL PROPERTIES	STANDARD	METRIC
---------------------	----------	--------

Tensile Strength	70 lbs/in width	122.6 N/10 mm
Adhesion to Stainless Steel	83 oz/in width	9.08 N/10 mm
Thickness	12.5 mils	0.32 mm
Elongation	6%	6%
Service Temperature Range	50 F to 180 F	10 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

