

## 20" Traction Drive Walk-Behind Scrubber

The Sentry 202T boasts a complete set of features, including a traction drive system. It excels in various environments including retail, education, and healthcare facilities. With a noise level of only 62dBA, it comfortably accommodates day-cleaning schedules. Its versatility and low noise make it an excellent choice for professional cleaners.

- Highly productive: Clean up to 35,500 square feet per hour. Its generous 10.6 gallon solution tank allows operators to get more done with fewer trips to refill the machine.
- Exceptionally Quiet: At 62dBA, the Sentry 202T stands out in its class. Suitable for day-cleaning and healthcare environments.
- Eco Mode: A single button push puts the machine into a water saving mode that reduces cleaning solution usage, energy, and noise.
- Extensive Feature List: The Sentry 202T has a robust set of features, including hygienic tanks, front and rear fill ports, breakaway squeegee design, corrosion resistant brush deck, and more.



## SPECIFICATIONS

# SENTRY 202T

Specifications	Item #	HIL56102WET
Cleaning Path	In	20
Squeegee Width	In	27.8
Disc Brushes	(No.) In	(1) 20
Solution Tank	Gal	10.6
Recovery Tank	Gal	13.2
Battery Pack Voltage	V	24
Acoustic Level (Iso 11201)	Db (A)	62
Traction Motor	V/W	24 / 150
Forward Speed	MPH	2.5
Brush Motor(s)	(No.) V/W	(1) 24 / 500
Vacuum Motor	V/W	24 / 410
Brushes RPM	RPM/Min.	140
Brush Pressure	Lb	51
Productivity	Sqft/Hr	35,521
Battery Compartment Dimensions (L,H,W)	In	13 x 14.1 x 9
Battery Type		Flooded Lead-Acid
Batteries	(no) V/Ah	(2) 12/105
Charging System		Onboard
Machine Dimensions (L,H,W)	In	46.0 x 39.8 x 23.2
Machine Weight (Without Battery)	Lb	135
Contents		1 - Medium Polypropylene Brush 1 - Pad Holder 1 - Set of Battery Cables
Brush Options		Soft PPL Brush, 0.3mm (HIL404654) Medium PPL Brush, 0.6mm (HIL405631) Firm PPL Brush, 0.9mm (HIL404653) Abrasive 80 Grit Brush (HIL405632)
Warranty		- Lifetime Tanks - Parts: 3 years - Service: 1 year - Travel: 1 year



1. Simple, intuitive control panel for easy training and use.
2. Large recovery tank lid to allow thorough rinsing after use.
3. Front and rear fill ports.
4. Internal vacuum motor housing reduces noise to just 62 dBA.
5. A ball float protects the vacuum motor, easily removable for cleaning.
6. A solution tank filter prevent clogging by capturing foreign materials.
7. Corrosion resistant brush head and squeegee support.
8. The recovery tank slopes to the rear for complete draining.
9. Break-away squeegee mount protects the machine.



SCAN FOR INFO



**HILLYARD**  
The Cleaning Resource®

PO Box 909  
St. Joseph, MO 64502  
www.hillyard.com

LIT-SENTRY-202T-0724

Subject to change without notice.