



### Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

### Directions for Use

DIRECTIONS: Dilute product according to label directions. Allow solution to penetrate soil for 5 minutes. Rinse thoroughly with clean water. Can use with brush cleaning. Light cleaning: Dilute 1oz. HV-Pro into 1 gallon of water. Medium Cleaning: Dilute 3oz. HV-Pro into 1 gallon of water. Heavy Cleaning: Dilute 6oz. HV-Pro into 1 gallon of water

An industrial vehicle wash specifically formulated for hand vehicle washing systems. HV-Pro removes most exhaust deposits, road film, and bug residue from painted vehicle surfaces, cleans aluminum siding, painted wood, and painted metal surfaces. HV-Pro rinses residue-free and water will bead up for that just waxed look. For use with hot or cold water, HV-Pro is heat stable to 180° Fahrenheit, and contains no solvents, free acids or phosphates.

### Features & Benefits

Great foaming characteristics.

Effective in hot or cold water.

Can also be used in pressure washers.

### Item Number & Unit of Measure

Item Number	HIL0045309
Unit of Measure	55 gal Drum

### Specifications

Color	Green
Appearance	Clear
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	1:20 - 1:128
PH	8.00 - 9.50
Non-Volatile Matter	6.75 - 7.75%