



Coverage SqFt/Gallon	1500-2000
Dry Time (hrs.)	1
Sheen	Gloss

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Preparation: New floors: After resilient flooring has been installed and the adhesive has cured for at least 2 weeks, scrub with a solution of Hillyard Recoat Prep or Assurance®, following label directions, and a blue pad to remove factory finish. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse® and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. Scrub and recoat: Scrub the existing floor polish with a solution of Hillyard Recoat Prep or Assurance, following label directions, and a blue pad. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. Stripping: Strip Navigator or other polishes from the floor with a solution of Hillyard Arsenal® Stripper, Devastator®, or Power-Strip®, following label directions. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. **Application:** When using a sealer, apply a minimum of 4 coats of Navigator at a rate of 1500-2000 ft²/gallon with a microfiber flat finish mop or Multi-Flo® XP. Allow each coat to dry a minimum of 45 minutes to 1 hour before applying the next. When a sealer is not used, apply a minimum of 6 coats of Navigator. **NOTE:** Allow for longer dry

Navigator utilizes the latest advancement in acrylic polymer technology to deliver a protective floor coating that offers excellent clarity and durability. Navigator provides excellent resistance to scuffing, scratching, and heel marking. Navigator's optimal solids content makes it extremely easy to apply resulting in even, clear protective layers of finish for your floor.

Features & Benefits

Holds up to the most severe traffic

Clarity - Will not discolor even after months of wear

Easy to clean

Item Number & Unit of Measure

Item Number	HIL0053606
Unit of Measure	1 gal Bottle

Specifications

Color	White
Appearance	Milky Emulsion
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	RTU
PH	8.00-9.00
Non-Volatile Matter	19.50-20.50%
Solids Content	20

time between coats of finish if the humidity is above 80% or the floor temperature is below 60 °F (16°C). For best results, do not apply more than 3-4 coats per day. **Maintenance:** Use a cotton dust mop, treated with Hillyard Super Hil-Tone®, daily to remove loose dirt and grit. Damp mop or autoscrub, as scheduled, with Hillyard Super Shine-All®, Top Clean®, or Arsenal® Heavy Duty Floor Cleaner. After the floor has been cleaned, gloss may be restored by spray buffing with Hillyard Hil-Glo®, according to label directions. Scrub and recoat, as scheduled, with a minimum of 2 coats of Navigator. **FLOOR PAD**

RECOMMENDATIONS: Stripping: black; **Scrub and Recoat:** blue; **Autoscrubbing:** red **NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is very porous, seal with Hillyard Hil-Tex+, Seal 341® or Seal 340® before applying Navigator. If stains are a problem, seal with Strong Guard®. Do not pour unused finish or seal back into the original container.