



CRC Industries NZ  
Auckland NZ

## I. Product Description

CRC Tackleguard is specifically formulated to keep fishing tackle safe from corrosion. It cleans, lubricates, drives out moisture, prevents corrosion and protects tackle even through periods of storage.

A light spray once a day during fishing is recommended. At the end of the season or earlier if heavy use or continuous exposure to the elements occurs reels should be taken apart, cleaned and lubricated then liberally sprayed with CRC Tackleguard.

## II. Features & Benefits

- **Fights corrosion** – Protects all metal reel parts, terminal tackle, rod guides and knives from corrosion
- **Lubricates** – Protects and lubricates all types of fresh and salt water reels
- **Nylon and mono fishing line safe formula** – Will not damage monofilament, EVA Grips, seals, nylons, rubbers, etc. Use with confidence.
- **Displaces water** – Penetrates and drives out moisture leaving a long-lasting film that will not dry out
- **Penetration levels designed to loosen corroded parts yet not penetrate into gears**
- **Rust free can** – Will not discolour surfaces or stain hands
- **Small can size** – Fits tackle boxes and small storage areas
- **Clean fresh smell** – Will help overcome stale fish smell
- **Concentrated spray pattern** – For economical delivery
- **Designed in New Zealand for New Zealand conditions**

## III. Application and Directions

1. Shake can well before using.
2. Spray a light even coating.
3. Use minimum amount necessary, remove excess with a clean cloth.

## IV. Typical Properties and Characteristics

### Physical Properties:

|                  |                   |
|------------------|-------------------|
| Flash Point      | 300 °C TCC        |
| Appearance       | Colourless liquid |
| % Volatile       | Nil               |
| Specific Gravity | 0.88              |
| Propellant       | Hydrocarbon       |

### Performance Characteristics:

|                   |                   |
|-------------------|-------------------|
| Type of film      | Thin, oily film   |
| Dry Time          | Non-drying, wet   |
| Timken OK Load    | 40lb              |
| Temperature Range | -40 °C to +180 °C |



CRC Industries NZ  
Auckland NZ

## V. *Package Description*

| Part Number | Size          |
|-------------|---------------|
| 6028        | 130ml Aerosol |

## VI. *Special Precautions*

### **General:**

Combustible liquid. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or with adequate ventilation. Store in a well-ventilated place. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

### **Aerosol Cans:**

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### **First Aid:**

Swallowed – Avoid giving milk or oils or alcohol. Not considered a normal route of entry.

Skin – Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.

Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay.

Inhaled – Remove to fresh air. Lay patient down. Keep warm and rested.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 03/2012

**PRODUCT WARRANTY:** CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

**DISCLAIMER:** All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.