



Annual Test Data

Chrysler

Specification: MS-CC244 Rev: C Lab: 3M Lab
Product: 467MP Lot#: 15062 Substrate: ABS

QUALIFICATION DATA

<u>TEST</u>	<u>TEST METHODS</u>	<u>SPECIFICATION</u>	<u>RESULT</u>
Environmental Aging Heat Aging	MS-CC244	no evidence adhesive softening, exudation, embrittlement, loss of bond, deterioration, or effects of the overlay or substrate material	Pass
Condensing Humidity Exposure		no evidence adhesive softening, exudation, embrittlement, loss of bond, deterioration, or effects of the overlay or substrate material	Pass
Cycle Test		no evidence adhesive softening, exudation, embrittlement, loss of bond, deterioration, or effects of the overlay or substrate material	Pass
Peel Adhesion, 90 degree Heat Aging	MS-CC244	0.53 kN/cm (3.0 lb/in.)	1.64 (9.37)
Condensing Humidity		0.53 kN/cm (3.0 lb/in.)	1.16 (6.62)
Cycle Test		0.53 kN/cm (3.0 lb/in.)	1.08 (6.17)

Qualification Data Tested : 2/25/98

ANNUAL CERTIFICATION DATA

<u>TEST</u>	<u>TEST METHODS</u>	<u>SPECIFICATION</u>	<u>RESULT</u>
Thickness		0.05 +/- 0.01 mm (0.0016 - 0.0024 in)	0.049 mm (0.0018 in)
Adhesive Softening Point	CP-463TB-14-01	79C	>82 C
Peel Adhesion, alum. backing 20 min dwell 24 hrs @ RT	ASTM D3330 C	0.35 kN/cm (2.0 lb/in) 0.53 kN/cm (3.0 lb/in)	0.53 N/mm (3.0 lb/in) 0.64 N/mm(3.65 lb/in)
Peel Adhesion, alum. backing (face side) 20 min dwell 24 hrs @ RT	ASTM D3330 C	0.35 kN/cm (2.0 lb/in) 0.53 kN/cm (3.0 lb/in)	0.46 N/mm (2.65 lb/in) 0.68 N/mm (3.91 lb/in)

* Aluminum backing used under waiver

Data Test Date: 06/30/2014

Approved by IATD Quality:

Huy Ho
Test Coordinator
Office: (651)737-6071
Fax: (651) 737-5477

Important notice to purchaser All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed, and

the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and manufacturer's only obligation shall be to replace such quantity of product to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Neither seller nor manufacturers shall be liable either in tort or in contract for any loss or damage, direct, incidental, or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller or manufacturers.