



NOTES:

1. MATERIALS:  
FRONT BODY: BERYLLIUM COPPER PER ASTM B196  
REAR BODY AND CONTACT: BRASS PER ASTM B16  
INSULATORS: TEFLON PER ASTM D1710
2. FINISH:  
BODIES: .000015 MIN. GOLD PER MIL-G-45204 OVER  
.000050 MIN. NICKEL PER QQ-N-290  
CONTACT: .000030 MIN. GOLD PER MIL-G-45204 OVER  
.000050 MIN. NICKEL PER QQ-N-290
3. FOR USE WITH .047 SEMI-RIGID CABLE.
4. FOR ASSEMBLY USE CAP 5-08 WITH ABOVE TRIMMING DIMENSIONS.

THIS INFORMATION IS PROPRIETARY AND CONFIDENTIAL. IT IS DISCLOSED TO YOU ON CONDITION NO FURTHER DISCLOSURE IS MADE TO OTHER THAN RETCONN PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM RETCONN INC., TORRINGTON, CT.

UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE NOMINAL AND  
FOR REFERENCE ONLY.  
DIMENSIONS IN INCHES  
DO NOT SCALE PRINT

**SALES DRAWING**



**RETCONN**

A SUBSIDIARY OF SPM  
199 W. PEARL ROAD TORRINGTON, CT. 06790  
TEL. (860) 499-1220 FAX (860) 496-7307

TITLE					
MCX RIGHT ANGLE PLUG					
DRAWN	DATE	CHECKED	SCALE	FSCM (REV)	
KJT	6/30/97	JMC	8:1		
APPR.	DWG. NO.				
AT	452-500-0470H				

REV.	DESCRIPTION OF CHANGE	DATE	DRN	APPR	MATERIAL	FINISH
B	ECN 2204	3/3/99	JED	YJB		
REVISIONS						