

CyberPower

GX1005C2
GAMING SURGE
PROTECTOR

Protects high end electronics from
power interruptions and power surges.

Level up your defense with the CyberPower GX1005C2 Surge Protector – built for gamers who don’t mess around. Packing a whopping 3000 joules of protection, it shields your battle station from power spikes, surges, and the chaos of the grid. Whether you’re running raids on your console or racking up kills on your PC, your gear stays locked and loaded. With ten total outlets (including four wide-spaced for chunky plugs), a five-foot cord, and dual USB-C ports for fast charging, you can power your rig, dual monitors, charging docks, VR base stations, and still have room to spare—no more playing outlet Tetris. And the customizable RGB light bar? It syncs with your setup so your surge protector doesn’t just protect—it flexes. Backed by a one-year warranty and a \$300,000 Connected Equipment Guarantee, the GX1005C2 is your shield against power chaos. Defend your gear. Light up your loadout. Stay in the game.



TYPICAL APPLICATIONS

- Gaming Systems

FEATURES

- AC Outlets: 10
- Cord Length: 5 ft
- Surge suppression: 3000 J
- Plug type: NEMA 5-15P
- Plug style: Right angle, 45° offset
- Outlet type: NEMA 5-15R
- USB-C charge ports: 2
- USB-C charge output: 18W total
- Volts: 125 V
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000

SPECIFICATIONS

INPUT	
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	45° Offset Right

OUTPUT	
Outlet Type	10 x NEMA 5-15R
USB Charge Port Type	2 x Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts

GX1005C2

GAMING SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz / 100 MHz
Maximum Surge Current	75,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	15,000 A
Response Time	<1 Nanosecond
Surge Suppression	3000 J
PHYSICAL	
Color	Black
Form Factor	Strip
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	12.95 x 3.3 x 26.97 cm
Physical Dimensions - Width/Height/Depth (mm)	130 x 33 x 270 mm
Physical Dimensions - Width/Height/Depth (in.)	5.1 x 1.3 x 10.62 in.
Weight (kg)	0.63 kg
Weight (lb)	1.38 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	14.0 x 30.99 x 7.8 cm
Shipping Dimensions - Width/Height/Depth (mm)	139.95 x 309.88 x 77.98 mm
Shipping Dimensions - Width/Height/Depth (in)	5.51 x 12.20 x 3.07 in.
Weight (kg)	0.75 kg
Weight (lb)	1.65 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL UL1363 UL1449 DOE VI FCC
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty