

Kubos™ EasyInstall Universal Shower Combination

MODELS:

- SLV-1310-UNI: 1.75 GPM (6.6 L/min) Flow Rate Shower Head
- SLV-1310-UNI-E2: 2.0 GPM (7.6 L/min) Flow Rate Shower Head

FEATURES:

- CPT-1300-UNI: Universal Shower Valve Trim
- S-5001-E175: Kubos Exhilaration 5 Function Shower Head
1.75 GPM (6.6 L/min) Flow Rate Shower
- S-5001-E2: Kubos Exhilaration 5 Function Shower Head
2.0 GPM (7.6 L/min) Flow Rate Shower Head
- S-2560: Shower Arm and Flange

VALVE OPTIONS:

- Retrofittable to:
 - Kohler® Rite-Temp® K-304-KS valve
 - Moen® PosiTemp® 62370 valve
 - Delta® R10000-UNWS valve
 - Symmons® 46-2-X-BODY Temptrol® valve
 - Pfister JX8/OX8 Valve (Add-On Kit RPG10-0113)

ADD-ON:

- RPG10-0113: Pfister JX8/OX8 valve installation kit

STOCK FINISHES:



PC BN MB

STANDARDS:

- ADA compliant
- WaterSense: S-5001-E175 & S-5001-E2


WARRANTY:

Visit www.speakman.com for full product warranty information

- See Speakman.com For Warranty Information


Retrofits to:

MOEN




MOEN® Posi-Temp®
2510
2520
2570
2580
2590

DELTA




DELTA® MultiChoice®
R10000-UNBX
R10000-UNBXH F
R10000-UNWS
R10000-UN
R10000-UNWSHF

KOHLER




KOHLER® Rite-Temp®
K-304-CS-NA K-304-US-NA
K-304-CX-NA K-304-UX-NA
K-304-PS-NA K-304-K-NA
K-304-PX-NA K-304-KS-NA

SYMMONS



SYMMONS® Temptrol®
4000-BODY
4000-X-BODY
46-2-X-BODY

PFISTER




PFISTER Valve
JX8 OX8



Information continues on next page

Kubos™ EasyInstall Universal Shower Combination



1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified all inlets and outlets are 1/2" female copper sweat and 1/2" male NPT. 3. For ADA mounting locations consult ADAAG, ANSI A117.1 or state regulations.

Architect/Engineer Approval Space:

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: 04-FEBRUARY 2024