

# LEAD FREE BRASS BALL VALVES



## JF-100SG-LH

2 Piece, Full Port, Solder Connection, Stainless Steel Trim, Locking Handle, 600 WOG



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
100-113SSG-LH	1/2"	100	10	45
100-114SSG-LH	3/4"	80	10	67
100-115SSG-LH	1"	48	8	53
100-116SSG-LH	1-1/4"	36	4	68
100-117SSG-LH	1-1/2"	24	2	62
100-118SSG-LH	2"	12	3	47
100-119SSG-LH	2-1/2"	6	1	44
100-120SSG-LH	3"	6	1	55
100-121SSG-LH	4"	2	1	35

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372
- FM Approval (1/4" - 2")
- Wetted Surfaces Contain Less than .25% Lead Content



## JP-150G

2 Piece, Full Port, Press Connection, 250 WOG



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
150-203G	1/2"	100	10	54
150-204G	3/4"	60	10	52
150-205G	1"	36	6	49
150-206G	1-1/4"	24	4	50
150-207G	1-1/2"	10	1	38
150-208G	2"	4	1	24

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- Wetted Surfaces Contain Less than .25% Lead Content



## JP-150G XLC

2 Piece, Full Port, Press XLC Connection, 250 WOG



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
150-209XLCG	2-1/2"	4	1	24
150-210XLCG	3"	4	1	24
150-211XLCG	4"	4	1	24

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- Wetted Surfaces Contain Less than .25% Lead Content

