



Technical Data Sheet

3M[™] Scotch[®] Specialty Performance Film Tape 8004

Product Details



Product Description

Scotch® Specialty Performance Film Tape 8004 is designed for lifting and preserving physical evidence such as finger prints. This ultra clean tape is resistant to moisture and resists degradation due to sunlight exposure and extended storage, and it is dimensionally stable up to continuous 225°F (107°C). The adhesive resists oozing and has good adherence to most smooth surfaces with an easy unwind.

Product Features

- Easy to unwind.Long aging.
- Easy hand tear.
- Handles easily.
 Quick stick for lifting.
- Preserves important information.
- Optical clarity.
- Resist puckering, yellowing, and drying out.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value	
Adhesive Type		Transparent pressure sensitive acrylic	
Backing		Polypropylene film	
Backing Thickness	ASTM D3652	0.036 mm (1.4 mil)	
Total Tape Thickness	ASTM D3652	0.051 mm (2 mil)	

Typical Performance Characteristics

Attribute Name	Test Method	Temperature	Value
180° Peel Adhesion	ASTM D3330	22 °C (72 °F)	1.7 N/cm (16 oz/in) ¹
Elongation at Break	ASTM D3759		90 %
Longitudinal Tensile	ASTM D3759		21.5 N/cm (19 lb/in)
Strength			31.5 N/cm (18 lb/in)

¹ 12 in/min (300 mm/min)

Storage and Shelf Life

Storage of tape at 70°F (21°C) and 40 to 50% relative humidity is recommended. To obtain best performance, use this product within 18 months from date of manufacture.

Available Sizes

Attribute Name	Value
Core Size (ID)	25.4 mm (1 in)
Standard Roll Length	9 m (10 yd)
Standard Width	25.4, 38.1, 50.8, 76.2, 101.6 mm (1, 1.5, 2, 3, 4 in)

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M Closure and Masking Systems Division 3M Center, Building 225-35-06 St. Paul, MN 55144-1000 800-362-3550 • 877-369-2923 (Fax) www.3M.com Scotch is a registered trademark of 3M. © 3M 2009 (8/09)