

## 4" TWO-WAY CEILING-MOUNT LOUDSPEAKER

### CM4PR

#### 3-1/2" Two-Way Ceiling-Mount Performance Loudspeaker

For smaller spaces or wherever preventing sound bleed-through to other spaces is critical



Stock Number

FG01666

Packaged Individually  
with Round MicroThin Grille

#### FEATURES

- Custom Rear Wave Enclosure enhances acoustic performance while limiting sound from bleeding through to adjacent spaces
- 3 1/2" Mineral-Filled Polypropylene cone woofer is extremely rigid to reduce breakup, lower distortion and provide enhanced bass response
- Butyl rubber surround damps resonance and provides exceptional durability
- 1" fluid-cooled Teteron® dome tweeter offers ultra-wide dispersion and silky-smooth high-frequency response
- Easy-to-use Tri-mount clips provide for quick installation
- Magnetically attached, rust-resistant grille covers install quickly and provide a low-profile look
- Weather-resistant construction reduces installation limitations and provides unique solutions in moist environments or outdoors under eaves

#### SPECIFICATIONS

- Frequency Response: 70Hz to 21kHz +/-3dB
- Impedance: 8 ohm nominal; 6 ohm minimum
- Recommended Amplifier Power: 25 to 100 Watts
- Hole Cutout Size: 4-5/8" (11.75 cm)
- Depth behind ceiling (5/8" drywall): 3-5/16" (8.4 cm)

**Warranty: Lifetime Limited**

## 4" CEILING-MOUNT LOUDSPEAKER ACCESSORIES

### SG4C

#### 4" Square MicroThin™ Grilles



- Corrosion-resistant MicroThin™ grille material
- Can be painted to match room color

Packaged in Pairs

Stock Number

FG01674

### NCB4C

#### 4" New Construction Bracket



- Arms with center marking lines to allow visual adjustment to stud

Packaged in Pairs

Stock Number

FG01673