

# PEX Quarter-Turn Angle Supply Stop Valves

Job Name \_\_\_\_\_  
 Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Contractor \_\_\_\_\_  
 Tag \_\_\_\_\_ PO# \_\_\_\_\_

## Specifications

- Chrome plated finish

## Applications

- Hot & Cold Water Lines

## Materials

- C46500 Brass

## Dimensions and Product Offering

| Part Code     | Connections                   | Working Pressure | Working Temperature | A              | B     | C           | D     | E     |
|---------------|-------------------------------|------------------|---------------------|----------------|-------|-------------|-------|-------|
| <b>S10314</b> | 1/2" PEX x 3/8" OD Comp       | 100 psi          | 40°F - 160°F        | 1/2" PEX F1807 | 0.38" | 0.94 ±0.02" | 2.17" | 2.01" |
| <b>S10336</b> | 1/2" PEX x 1/4" OD Comp       | 100 psi          | 40°F - 160°F        | 1/2" PEX F1807 | 0.26" | 0.94 ±0.02" | 2.17" | 2.05" |
| <b>S10340</b> | 1/2" PEX F1960 x 3/8" OD Comp | 125 psi          | 40°F - 160°F        | 1/2" PEX F1960 | 0.38" | 0.94 ±0.02" | 2.21" | 2.01" |



F1807



F1960

## Certifications/Listings/Approvals

- NSF/ANSI 14 certified
- NSF/ANSI/CAN 61 certified
- NSF/ANSI/CAN 372 certified
- ASME A112.18.1/CSA B125.1
- SDWA compliant
- IAMPO listed
- Vermont Act 193 Compliant
- Lead Law Compliant

