Flexshaft K9-306 **RANGE OF ACCESSORIES**



HOOSING THE RIGHT

RIDGID® FlexShaft® Machines utilize specialized accessories attached to a flexible cable that are spun at high speeds for effective wall-to-wall cleaning action. Selecting the correct chain knocker or brush for your application and pipe material will ensure an efficient clean-out.

CLEANING V. CLEARING

MAINTENANCE AND RELINING

Chain knockers deliver wall-to-wall clean and can get pipes working like new, creating opportunities for warranties or up charges. Total cleaning also lets you prepare damaged pipe for relining as an alternative to digging and replacing.

EMERGENCY BLOCKAGES

When an emergency blockage needs to be cleared to get water running and the client doesn't want to pay for total pipe cleaning, just clearing the blockage is also a solution.



SMOOTH CHAIN KNOCKERS For all pipe types For soft blockages



PIPE WALL CLEANING

CHAIN KNOCKERS

CARBIDE TIPPED CHAIN KNOCKERS

 For hard-walled pipes For scale, roots, grease and soft blockages

PENETRATING, **CARBIDE TIPPED CHAIN KNOCKERS**

For hard-walled pipes For wipes, scale, roots and soft blockages

BRUSHES





NYLON BRUSH

- Gentle cleaning of fragile pipes
- Centering guide for other tools ō
- For spreading resin when ٠ spray lining
- For final cleanup to sweep fine debris downstream

NYLON-STEEL BRUSH

- For cleaning & light grinding ė
- For relining preparation of PVC & cast iron pipes
- For final cleanup to sweep fine ۲ debris downstream

PENETRATING TIP



PENETRATING TIP

 Penetrating tip functionality with smooth chains when carbide tipped chains are too aggressive



FLEX YOUR COVERAGE.

K9-306 MACHINE

RIDGID

0

Use the table below for recommended options based on blockage, pipe size and pipe type.

FlexShaft[®] K9-306

Ø AN

		K9-306 MACHINE										
					Contra La Contra			Ø	Ø	Ø		
		Chain Knockers		Carbide Tipped Chain Knockers			Penetrating Head Chain Knockers			Penetrating Tip		
	CATALOG NO.	66618	66623	66628	66633	66638	66643	66648	66653	66658	71858	
	DESCRIPTION	K9-306 3"	K9-306 4"	K9-306 6"	K9-306 3" CARBIDE	K9-306 4" CARBIDE	K9-306 6" CARBIDE	K9-306 - 3" PENETRATING HEAD	K9-306 - 4" PENETRATING HEAD	K9-306 - 6" PENETRATING HEAD	K9-306 PENETRATING TIP	
	PIPE SIZE (inch / mm)	3"- 4" (76-102 mm)	4"-5" (102-127 mm)	5"- 6" (127-152 mm)	3"- 4" (76-102 mm)	4"-5" (102-127 mm)	5"- 6" (127-152 mm)	3"- 4" (76-102 mm)	4"-5" (102- 127 mm)	5"- 6" (127-152 mm)	6" (150 mm)	
PIPE TYPE	COPPER				\odot	\oslash	\odot	\odot	\oslash	\odot	\odot	
	GALVANIZED				\odot	\oslash	\odot	\odot	\odot	\odot	\odot	
	CAST IRON				\odot	\odot	\odot	\odot	\odot	\odot	\odot	
	PVC	\odot	\odot	\odot							\odot	
	ABS	\oslash	\odot	Ø							\oslash	
	ORANGEBURG	Ø	\odot	Ø							\oslash	
	CORRUGATED	\odot	\odot	Ø							\odot	
	CLAY	\odot	\odot	Ø							\odot	
	GREASE	Ø	\odot	\odot	Ø	\oslash	\odot	Ø	\oslash	Ø	Ø	
BLOCKAGE	SOFT BLOCKAGE	\oslash	\odot	\odot	\oslash	\oslash	\odot	\oslash	\oslash	\odot	\oslash	
	SCALING				\odot	\odot	Ø	Ø	\odot	Ø		
	ROOTS				\odot	\odot	\odot	\odot	\odot	\odot		
	WIPES							Ø	\odot	\odot	\odot	
	INCLUDED WITH KIT		\odot	Ø								

RIDGID

Any accessory can be purchased separately.



FlexShaft[®] *k9-306* FIND THE RIGHT **BRUSH** TO CLEAN AND PREPARE DRAINS WALL-TO-WALL

K9-306 MACHINE			K9-306 MACHINE								
				NYLON BRUSH		N N	YLON AND STEEL BRU	SH			
APPLICATION			Suitable as a central sector of the secto	r gentle cleaning of f tering guide for othen ading resin when spra	tools	 Nylon – Steel material for cleaning & light grinding Suitable for relining preparation of PVC and cast iron pipes 					
	CATALOG NO.		68958	68963	68968	68988	68993	68998			
	PIPE SIZE (inch / mm)		3" (75 mm)	4" (100 mm)	6" (150 mm)	3" (75 mm)	4" (100 mm)	6" (150 mm)			
	COPPER Galvanized			\odot		\odot					
				\odot		\odot					
	CAST IRON			\odot		0					
CHING	RIAL	PVC		\odot		\bigcirc					
BRUSH MATCHING	ABS ABS ABS ABS ABS			\odot		\bigcirc					
BRUS	ЫР	ORANGEBURG		\odot							
	CORRUGATED			\odot							
	CLAY			\odot							
		PORCELAIN		\odot							
	BRUSH DIAMETER (inch / mm)		3" (75 mm)	4" (105 mm)*	6" (155 mm)*	3" (75 mm)	4" (105 mm)*	6" (155 mm)*			
	CABLE DIAMETER (mm)		10	10	10	10	10	10			
SECURING RING Matching	CATALOG NO.			68928		68928					

*4" and 6" nylon - steel brushes need to have longer strings in order to provide a thorough cleaning

