



7050SG Home/Office Surge Protector

Offering home/office environments with computer and communication grade surge protection.

The CyberPower 7050SG is a Home/Office Computer Surge Protector with seven (7) total surge protected outlets and three (3) Energy-Saving outlets designed to turn off up to three connected devices when your computer is shut down or goes into standby mode. With RJ11 (1 in / 2 out) phone/fax/modem protection, the CyberPower 7050SG surge protector is ideal for personal computers, phones/fax/modems, printers, speakers, scanners and home electronics.

The 7050SG features 2250 Joules of protection and metal oxide varistor (MOV) technology, which guards the surge protector and connected electronics against line abnormalities and lightning surges. EMI/RFI filtering blocks unwanted line noise from all connected electronics.

A Limited Lifetime Warranty ensures that this surge protector has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$250,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Routers & Modems
- Personal Electronics

Features

- 7 Surge Protected Outlets
- 3 Energy-Saving Outlets
- 2250 Joules of Surge Protection
- DSL / Phone / Fax Protection – RJ11
- 15A Circuit Breaker
- 5 ft. Cord
- EMI/RFI Noise Filters
- Lifetime Warranty

7050SG Home/Office Surge Protector

Offering home/office environments with computer and communication grade surge protection.

GENERAL	
Product Type	Surge Protector
INPUT	
Voltage	125V
Circuit Breaker	15 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle
Cord Length	5'
OUTPUT	
Outlets - Total	7
Outlet Type	NEMA 5-15R
Outlets - Energy Saving	3
Outlets - Widely Spaced	1
SURGE PROTECTION & FILTERING	
Surge Suppression	2,250 Joules
Maximum Surge Current	105,000 Amps
Maximum Surge Current H-N	45,000 Amps
Maximum Surge Current H-G	30,000 Amps
Maximum Surge Current N-G	30,000 Amps
Clamping Voltage	330V (L-N) 400V (L-G, N-G)
Response Time	< 1 nanosecond
Phone Protection RJ11	1-In, 2-Out
EMI/RFI Filtration	Yes
Attenuation	Up to 43dB
INDICATORS	
Indicators	Protected (Green), Grounded (Green)
CERTIFICATIONS	
Safety	UL1449
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Limited Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$250,000