



See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

IMPORTANT: Clean up tools and equipment immediately after use. Do not leave in solvent overnight. **NOT TO BE USED AS A THINNER.** HILLYARD products are formulated to be used as they come from the container. **NOTICE:** Emptied containers may retain hazardous residue and explosive vapors. Keep away from heat, sparks, and flames. Do not cut, puncture, or weld on or near this container. Follow label warnings until container is thoroughly cleaned or destroyed. **NOTICE:** Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building. **NOTICE:** Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

A special blend of highly refined solvents designed for tack ragging raw wood or between coats of seal and finish. It removes dust and dirt which may have settled on the surface and helps ensure good adhesion between coats. It is also perfect for cleaning tools and equipment used to apply solvent based waxes, seals, and finishes.

Features & Benefits

Highly refined solvents evaporate quickly to save time and have a more efficient process

Leaves NO oily residue and leaves floors ready

Only 30 minutes dry time is needed before applying coating

Item Number & Unit of Measure

Item Number	HIL0043707
Unit of Measure	5 gal Pail

Specifications

Color	Colorless
Appearance	Clear
Fragrance	Mineral Spirits
Formula Type	Liquid
Dilution Ratio	RTU
Non-Volatile Matter	0.00%

Safety