



Maintain luxury vinyl flooring with Hil-Sheen LV, Hillyard's cleaning solution designed explicitly for Luxury Vinyl Tile (LVT) and Luxury Vinyl Plank (LVP). Hil-Sheen LV cleans and rejuvenates your floors, bringing them back to life with a brilliant shine.

LVT and LVP floors can lose their gloss and develop scratches and blemishes. Hil-Sheen LV addresses these issues head-on, providing a simple yet effective solution beyond just cleaning. Unlike general hard floor cleaners, Hil-Sheen LV is specifically formulated to care for flooring by building a thin polymer layer with each use. Integrating Hil-Sheen LV into your regular cleaning routine ensures your LVT/LVP floors maintain their original beauty and shine, significantly delaying the need for costly replacements or restorative work.

Features & Benefits

While Hil-Sheen LV is designed with LVT/LVP in mind, it also provides outstanding cleaning power on VCT and other rubber or synthetic flooring materials.

Compatible with auto scrubbers and flat mops, making it convenient for regular use without the need for specialized equipment.

Consistent use keeps new floors looking fresh and revitalizes scratched flooring.

Perfect for high-traffic environments where floor longevity and appearance are paramount, such as healthcare and education.

Item Number & Unit of Measure

Item Number	HIL0014107
Unit of Measure	5 gal BIB

Specifications

Color	White
Appearance	Milky, white
Fragrance	Floral
Formula Type	Liquid
Dilution Ratio	1:64
РН	8.00 - 9.00
Non-Volatile Matter	7.00 - 8.00%

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

For use on LVT, coated VCT, sealed terrazzo, sealed concrete, and rubber flooring. NOT FOR USE ON WOOD FLOORS. Dilute Hil-Sheen LV 2 oz per gallon (1:64) with cool water. For heavily soiled floors, preclean with Hillyard Heavy Duty Floor Cleaner or Clean Scrub[®] HD for best results.

Automatic scrubber: Autoscrub all assigned flooring with a red scrub pad using overlapping passes while dispensing, agitating, and picking up the solution. Pick up any squeegee trails or puddles with a damp mop. NOTE: Do not allow Hil-Sheen LV solution to remain in the automatic scrubber tank. Drain and rinse. Hillyard Defoamer II is recommended for the recovery tank.

Damp mopping: For best results, damp mop with a microfiber flat mop. Do not overly saturate the floor. Mop the floor with overlapping passes. Allow the floor to dry. Change solution often if it becomes soiled.