

## HT806TC | HOME THEATER SURGE PROTECTOR

Protect home theater equipment, home and office computers, and other electronics

The Home Theater Surge Protector HT806TC provides 3,000 joules of surge protection and 8 outlets to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. RG6 coaxial connectors protect cable/satellite TV receivers and broadband modems.

Features of the HT806TC include automatic shutdown, 8 surge-protected outlets (4 widely-spaced for transformer plugs), a power cord (6 ft.), a right-angle plug with 45° offset, LED status indicators, keyhole mounting slots, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

### TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

### FEATURES

- Surge suppression: 3,000 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 8 x NEMA 5-15R
- Transformer outlets: 4
- Power cord: 6 ft
- Data line protection: Telephone, Coaxial
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$250,000



## SPECIFICATIONS

INPUT		OUTPUT	
Circuit Breaker	15 A	Outlet Type	8 NEMA 5-15R
Cord Length	6 ft (1.8 m)	Outlets - Total	8
Input Plug Type	NEMA 5-15P	Outlets - Widely Spaced	4
Maximum Input Current	15 A		

# HT806TC

## HOME THEATER SURGE PROTECTION

### SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING		DIMENSIONS	
Attenuation	30 dB	Physical Dimensions - WxHxD (cm)	13.0 x 3.99 x 31.5 cm
Clamping Voltage	500V (H-N, H-G, N-G)	Physical Dimensions - WxHxD (mm)	130 x 40 x 315 mm
Coax Protection RG6	1 In 1 Out	Physical Dimensions - WxHxD (in.)	5.12 x 1.57 x 12.4 in.
EMI/RFI Filtration	150 KHz 100 MHz Yes	Weight (kg)	0.61 kg
Maximum Surge Current	150,000 A	Weight (lb)	1.34 lbs.
Maximum Surge Current H-G	30,000 A	SHIPPING DIMENSIONS	
Maximum Surge Current H-N	90,000 A	Shipping Dimensions - WxHxD (cm)	3.18 x 36.83 x 15.24 cm
Maximum Surge Current N-G	30,000 A	Shipping Dimensions - WxHxD (mm)	31.75 x 368.3 x 152.4 mm
Maximum Surge Voltage	6,000 V	Shipping Dimensions - WxHxD (in.)	1.25 x 14.5 x 6.0 in.
Phone Protection RJ11	1-In / 2-Out	Shipping Weight (kg)	6.35 kg
Response Time	<1 Nanosecond	Shipping Weight (lbs.)	14.0 lbs.
Surge Suppression (Joules)	3,000 J	CERTIFICATIONS	
PHYSICAL		Environmental	RoHS Compliant
Color	Black	Safety	UL1449 3rd Edition cUL
Cord Management	Yes	WARRANTY	
Form Factor	Strip	CEG Amount	\$250,000
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)	Connected Equipment Guarantee	Lifetime
Keyhole Mounting Slots	Yes	Product Warranty	Limited Lifetime
Material of Construction	Plastic		
Safety Covers	Yes		