

3M

Industrial Protective Film

7070UV & 7071UV

Preliminary Technical Data

February, 2016

Product Description 3M™ Industrial Protective Films 7070UV and 7071UV are abrasion resistant, pressure sensitive adhesive backed film products designed to protect multiple industrial surfaces from damage caused by abrasion, scratching, erosion, UV and minor impacts. These rugged clear films are durable, flexible, and able to conform to curved surfaces while being easy to apply.

Product Construction	Backing	Adhesive	Liner
	Polyurethane	Acrylic	Paper

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

	7070UV	7071UV	ASTM Test Method
Total Thickness:	8 mils (0.20 mm)	14 mils (0.36 mm)	D-3652
Backing Thickness:	6.5 mils (0.17 mm)	12 mils (0.31 mm)	D-3652
Adhesive Thickness:	1.5 mil (0.4 mm)	2 mils (0.05 mm)	D-3652
Adhesion to Steel:	47 oz/in (51 N/100 mm)	52 oz/in (52 N/100 mm)	D-3330
Tensile Strength:	68 lbs/in (1162 N/100 mm)	55 lbs/in (963 N/100 mm)	D-3759
Elongation at Break:	656%	754%	D-3759
Liner Release:	10 g/in (0.39 N/100 mm)	17 g/in (0.66 N/100 mm)	D-3330

Features

- Abrasion resistant polyurethane backing resists punctures and tearing.
- Provided on a paper liner for ease of die cutting specific shapes.
- Easily applied with simple tools in a minimal amount of time.
- Clear color will not obscure surfaces.

Application Techniques

- For best results, surfaces must be clean and free of dirt, debris and oils and films should be applied when surface temperature is between 50°F (10°C) and 80°F (27°C).
- Use of an application solution is suggested for easy positioning and squeegee application.
- For detailed application instructions and tips, see 3M Technical Bulletin on installation of Industrial Protective Films.

3M™ Industrial Protective Film

7070UV & 7071UV

Storage

Keep film in a clean area, away from excessive moisture and out of direct sunlight. Store rolls under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

Shelf Life

To obtain best performance, use this product within 12 months from date of manufacture.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M

**Industrial Adhesives and Tapes
Division**

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



*Recycled Paper
40% pre-consumer
10% post-consumer*

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2016 (2/16)