

CyberPower

TR15U8A



5 USB (8.6A) Charger with Stand

Family-Sized: 8.6 amps through five ports lets you charge any combination of phones, tablets or other USB-charged devices simultaneously up to 2.4 amps per port or 8.6 amps overall. Ergonomic, compact and portable travel-ready design.

FEATURES

- Type: 5-Port USB Charger w/stand & 5' power cord
- Input: AC100V-240V
- Output: 5.25V-8.6A(max)
- USB: 5-Port

SPECIFICATIONS

| GENERAL | |
|--------------------------|---|
| Type | USB Charger |
| INPUT | |
| Input Connector Type | NEMA 1-15 |
| Input Voltage Range | 100-240Vac |
| Input current (Max.) | 1.2A |
| USB OUTPUT | |
| Output Voltage Range | 4.75 - 5.25 Vdc |
| USB Charging Ports | 5 |
| Output Current (Max.) | 8.6 Amp (Shared) |
| Output Protocol* | 2.4A guarantee for each port, Apple configuration Auto detect function reserved in design |
| Overload Protection | Internal Current Limiting |
| Over Current Protection | 9.3 |
| Short Circuit Protection | Yes |
| PROTECTION | |
| Short Circuit Protection | Yes |
| Overload Protection | Yes |
| Overheat Protection | Yes |

| LED INDICATION | |
|----------------------------------|----------------------------|
| LED Indication for Power On/ Off | Yes |
| PHYSICAL | |
| Housing Material | Plastic PC |
| Color | White/Grey |
| Dimensions (WxHxD) (in.) | 1.06 x 2.58 x 3.76 |
| Dimensions (WxHxD) (mm.) | 27 x 65.5 x 95.6 |
| Weight (lbs.) | .52 |
| Weight (kg.) | .24 |
| ENVIRONMENT | |
| Operating Temperature | 0° to 40° F / -18° to 5° C |
| CERTIFICATIONS | |
| Regulation | FCC Class B, UL60950 |
| RoHS compliance | Meet RoHS Europe standard |
| WARRANTY | |
| Product Warranty | 1 Year Limited |