

44001

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Mount the cross bar (1) to the outlet box (3) by using two outlet box screws (2).
2. Tie the ground wires (4&6) from fixture and from outlet box to the ground screw (5) on the cross bar (1). Connect the white fixture wire (11) from the fixture to the white wire (neutral wire 10) from the supply circuit. Connect the black fixture wire (9) from the fixture to the black wire (live wire 8) from the supply circuit.
3. Cover the connections using provided wire connectors (7). Position wires back inside outlet box.
4. Place the fixture body (12) over the cross bar (1).
5. Use a Phillips screwdriver (not included) to screw the sink screw (13) into the hole on the bottom of the fixture body (12) to secure it onto the cross bar (1).

6. To prevent moisture from entering the outlet box and the fixtures mounting plate causing a short, apply a bead of clear caulk to outline the outside of the fixtures mounting plate where it meets the wall. Leave a small space at the bottom to allow any condensation or moisture to escape.

7. Turn on power.

INSTALLATION IS NOW COMPLETED

