

DOUBLE-SIDED POLY-HANGING TAPE

TYPICAL APPLICATIONS

- For securing poly-sheeting, plastic drop cloths, tarps and other protective coverings when prepping for remodeling and renovation tasks such as painting, cleaning, sanding and more
- Can be used on a variety of surfaces, including painted walls and trim

PRODUCT FEATURES

- Hand-tearable and repositionable
- Conforms to uneven or irregular surfaces
- Removes quickly and easily in a single step
- Differential adhesive system – Exposed/Wall Side: Premium grade painter's tape adhesive that allows for 21-day clean removal from surfaces without damage or residue; Lined/Poly Side: Specially engineered aggressive adhesive that holds securely to poly-sheeting and other protective coverings

CONSTRUCTION

Overall Grade/Function: Professional
Backing: Fine structured crepe paper
Adhesive: Synthetic rubber
Liner: Super-calendered kraft (SCK)

STANDARD WIDTH(S)

36 mm

STANDARD LENGTH(S)

25 yd

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



NATURAL
(NAT)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	21 lbs/in width	36.8 N/10 mm
Adhesion to Stainless Steel (Exposed Side)	27 oz/in width	2.95 N/10 mm
Adhesion to Stainless Steel (Lined Side)	60 oz/in width	6.56 N/10 mm
Thickness	8.5 mils	0.18 mm
Elongation	9%	9%
Service Temperature Range	32 F to 120 F	0 C to 49 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

