



The perfect choice for cleaning and degreasing a variety of surfaces and items including air filters, concrete flooring, conveyors, exhaust hoods, walls, metal equipment, and machine parts.

Features & Benefits

High alkaline butyl-based formulation is exceptionally effective.

Authorized for use under NSF Category A1

Phosphate free, non-combustible

Item Number & Unit of Measure

Item Number	HIL0013711
Unit of Measure	275 gal Tote

Specifications

Color	Red
Appearance	Clear
Fragrance	Mild Solvent
Formula Type	Liquid
Dilution Ratio	1:128 - 1:1
PH	12.50 - 13.50
Non-Volatile Matter	12.50 - 13.50%
NSF_Certified	Yes

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Formulated to remove the toughest grease, oil, tar, and grime. Apply diluted KA INDUSTRIAL DEGREASER with a sprayer, brush, mop, or sponge, depending on the surface to be cleaned. May also be applied with pressure equipment and automatic scrubbers. Excellent for cleaning and degreasing air filters, concrete flooring, exhaust hoods, conveyors, walls, metal equipment and parts, and basically any hard surface not damaged by water. Rinse with hot or cold water. Phosphate free, non-combustible. LIGHT SOIL CONDITIONS: Dilute 1:128 (1 oz./gal. of water). AVERAGE SOIL CONDITIONS: Dilute 1:32 (4 oz./gal. of water). HEAVY SOIL CONDITIONS: Dilute 1:10 (12 oz./gal. of water). DEGREASING: Dilute 1:1 to 1:4 (32 oz./gal. of water). NOTICE: DO NOT USE ON GLASS.