

Yours for the masking...holding power, line sharpness, and removal the way you want

3M offers a complete family of crepe masking tapes for the industrial and consumer markets. Now buying just the right masking tape performance for every MRO job is as easy as asking for one of three masking tapes.

With these three crepe tapes, you have the range of holding power, line sharpness and clean removal that you need for MRO applications.

3M™ Masking Tape 231 provides best-in-class holding power for critical paint lines and clean removal on high valued products or processes.

With 3M™ Masking Tape 234 you get reliable masking and clean removal on surfaces for functional coatings or paints, splicing, and heavy duty maintenance.

3M[™] Masking Tape 2307 gives you clean removal for light duty bundling, attaching, and labeling.



Paint edge comparison



Slivering comparison

3M[™] Masking Tapes

Product	UPC # 021-200-	Size	Tape Structure (Backing/Adhesive)	Total Thickness mils (mm) (N/100 mm)	Adhesion oz/in. width (N/100 mm)	Tensile Strength Ibs./in. width	Elongation at Break %	Temp. Range °F (°C)	Packaging
231	03777-1	24 mm x 55 m	Natural colored crepe paper/ Rubber	7.3 (0.18)	35 (38)	28 (490)	8	Up to 300 °F (149°C) Up to 30 min.	36 per case
234	02982-0	24 mm x 55 m	Natural colored crepe paper/ Rubber	6.0 (0.15)	34 (37)	27 (472)	8	Up to 250 °F (121°C) Up to 30 min.	36 per case
2307	71118-3	24 mm x 55 m	Natural colored crepe paper/ Rubber	5.6 (0.14)	32 (34)	20 (350)	9	Up to 200 °F (93°C)	36 per case

NOTE: The technical information and data provided above is a general guide only and should be considered representative or typical only and should not be used for specification purposes

MRO Essentials – You could browse through the thousands of products at 3M to find time and work saving solutions for MRO tasks and problems. Or you could make one call to 1-800-362-3550 or go to the one site that focuses specifically on your needs. From abrasives to adhesives, masking tape to ear plugs, electrical connectors to cleaning products, simply click...

www.3M.com/industrial

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Business

