



PDU15SWHVIEC8FNET SWITCHED PDU



Designed for datacenters and other electrically demanding applications.

The CyberPower PDU15SWHVIEC8FNET, an 8-outlet (front), 1U rackmount switched power distribution unit (PDU), provides 200-240V 15A output. It distributes power to 8 IEC-320 C13 receptacles from a single IEC-320 C14 plug with unfiltered electrical pass-through. The switched outlet receptacles can be managed individually or collectively over the network, using the CyberPower Management Console, a web browser, and the RJ45 Ethernet port for network connection, or locally by using the LCD controls.

Outlets can be turned on, turned off, or recycled on demand or at programmed times to address a number of needs including remote rebooting of locked equipment, load shedding, power sequencing, and locking out unauthorized loads. The PDU15SWHVIEC8FNET comes with a three-year limited warranty that covers defects in materials and workmanship in the product under normal use and conditions within three years of the purchase date.

TYPICAL APPLICATIONS

- Servers
- Network Devices
- Telecom Equipment

FEATURES

- Switched PDU: SNMP Network Interface and Switchable Outlets
- Automated notifications: Email, SMS Text, and SNMP Trap
- Phase: Single
- Amps: 15A (Derated to 12A)
- Volts: 200 - 240 V
- Frequency: 50Hz/60Hz
- Plug type: IEC-320 C14
- Outlets: 8 IEC-320 C13
- Outlet location: 8 Front
- Size: 1U Rackmount
- Dimensions (in.): 17.05W x 1.75H x 4.41D
- Cord length (ft.): 10
- Warranty: Three-Year

SPECIFICATIONS

INPUT	
Cord Length	10 ft (3.0 m)
Input Frequency Range	50 Hz - 60 Hz
Input Plug Type	IEC-320 C14
Maximum Input Current	15A (Derated to 12A)
Plug Style	Straight

OUTPUT	
Meter Readout	Kilowatts Voltage Amperage IP Address
Nominal Output Voltage	200 - 240 VAC
Outlet Type	8 x IEC-320 C13
Outlets - Front	8
Outlets - Total	8
Overload Protection	15A (derated 12A - UL/10A-CE)

PDU15SWHVIEC8FNET SWITCHED PDU

SPECIFICATIONS CONT.

MANAGEMENT & COMMUNICATIONS	
Hardware Connection Port	RJ45 Serial
LED Indicators	Load Tx/Rx LINK Outlets
SNMP / HTTP Remote Monitoring	TCP/IP UDP DHCP SNMP HTTP

PHYSICAL	
Adjustable Mounting Brackets	2 sets (1 Short, 1 Long)
Color	Black
Cord Retention Tray Cord Organizers	Yes
External Site Ground Pin	Yes
Form Factor Supported	1U Rackmount OU Vertical Rackmount Undercounter Installation
Rack Height	1U
Style	Rackmount Vertical Rackmount Under-Counter

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	43.31 x 4.45 x 11.2 cm
Physical Dimensions - Width/Height/Depth (mm)	433 x 44 x 112 mm
Physical Dimensions - Width/Height/Depth (in.)	17.05 x 1.75 x 4.41 in.
Weight (kg)	1.9 kg
Weight (lbs.)	4.19 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	24.77 x 6.68 x 49.53 cm
Shipping Dimensions - Width/Height/Depth (mm)	247.65 x 66.8 x 495.3 mm
Shipping Dimensions - Width/Height/Depth (in.)	9.75 x 2.63 x 19.5 in.
Shipping Weight (kg)	3.81 kg
Shipping Weight (lbs.)	8.4 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 14,760 ft (0 - 4,499 m)
Operating Relative Humidity	0% to 95% non-condensing
Operating Temperature	32°F to 113°F / 0°C to 45°C
Storage Elevation	0 to 50,000 ft / 15,239 m
Storage Temperature	5°F to 113°F / -15°C to 45°C

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL60950_1 certified by ETL

WARRANTY	
Extended Warranty Option	WEXT5YR-PDU1A
Product Warranty	3-Year Limited