28601 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION


- 1. Secure the mounting plate (1) to the outlet box with the outlet box screws (2), then secure the plastic plug (3) and wood screws (4) to the wall.
- 2. Pull out the outlet wires and ground wire from the Outlet Box.

Make wire connections with Wire nut:

- ---Connect the white wire (Neutral wire) from light to the white wire from power source.
- ---Connect the black wire (Live wire) from light to black wire from power source.
- ---Wrap the grounding wire (green wire or bare copper wire) from the light around the green screw on the mounting bar (1), then connect it to the grounding conductor from power source.
- 3. Align the Back plate (7) to the Outlet box, then use a screwdriver (6) (not included) to secure it to the mounting bar (1) with the mounting screws (5).
- 4. Install type T bulb (9) (bulbs not included).

(Don't exceed the maximum capacity recommended on the sockets).

5. Attach the glass shade (10) to the fixture body (8).



INSTALLATION IS NOW COMPLETED