


BOX#1

A. HEADBOARD

I. LEG

1 PC 2 PCS





BOX#2

B. FOOTBOARD

I. LEG

1 PC 2 PCS





ī

BOX#3

C. SIDE RAIL

D. SLAT

E. CENTER SLAT SUPPORT

F. SIDE RAIL SLAT CLIP

G. CENTER SUPPORT SLAT CLIP

H. SLAT SUPPORT LEG

2 PCS


26 PCS

1 PC

26 PCS

13 PCS

2 PCS




HARDWARE KIT PACKED IN BOX #1

	1	ALLEN BOLT(5/16"x2-1/2")		2 PCS
	2	FLAT WASHER(3/4")		2 PCS
	3	LOCK WASHER(5/16")		2 PCS
	4	ALLEN KEY(5/16")		1 PC

HARDWARE KIT PACKED IN BOX #2

1	ALLEN BOLT(5/16"x1-1/4")	Manage	4 PCS
2	ALLEN BOLT(5/16"x2-1/2")		8 PCS
3	THREADED BOLT (5/16"x4-1/4")		8 PCS
4	FLAT WASHER(3/4")		8 PCS
5	LOCK WASHER(5/16")		12 PCS
6	ALLEN KEY(5/16")		1 PC
7	WRENCH(5/16")		1 PC
8	MENDING PLATE	0 0	4 PCS
9	HEX NUT(5/16")	\bigcirc	8 PCS
10	FLAT WASHER(1")		4 PCS

KIKI UPHOLSTERED BED FULLY ASSEMBLED













STEP 1


NOTE: USE HARDWARE PACKED IN BOX #1 FOR STEP 1.



STEP 2NOTE: USE HARDWARE PACKED IN BOX #2 FOR STEP 2 AND ALL STEPS THAT FOLLOW.



STEP 3




UPDATED:APRIL 26TH, 2023




(x2)





STEP 5






STOP


- IF USING BED WITH AN ADJUSTABLE MATTRESS BASE, SKIP STEPS6,7,8 & 9 AND REFERENCE APPENDIX A: ADJUSTABLE MATTRESS BASE ASSEMBLY SUPPLEMENT.
- IF USING BED FRAME WITH STANDARD BOX SPRING OR FOUNDATION, CONTINUE TO STEP 6.

STEP 6












STEP 8: STARTING FROM HEADBOARD









ASSEMBLY COMPLETE.


INSTRUCTIONS FOR ADJUSTING LEVELERS:

POSITION THE BED IN YOUR ROOM. LOCATE LEVELERS UNDER EACH SUPPORT LEG (H).

TURN COUNTER-CLOCKWISE TO EXTEND, CLOCKWISE TO RETRACT.

ADJUST LEVELERS UNTIL EACH LEG SUPPORT IS APPLYING EQUAL UPWARD PRESSURE ON THE CENTER SLAT.





MAINTENANCE INSTRUCTIONS:

- PERIODICALLY CHECK ALL FITTINGS AND TIGHTEN IF NECESSARY, AS THEY CAN LOOSEN OVER TIME.
- ALWAYS REMOVE BOX SPRING AND MATTRESS BEFORE MOVING THE BED.
- LIFT THE BED WHEN MOVING IT.
 DRAGGING THE BED CAN DAMAGE THE CENTER SUPPORT.
- READJUST LEVELERS AFTER MOVING THE BED.



APPENDIX A:ADJUSTABLE MATTRESS BASE ASSEMBLY SUPPLEMENT

AN ADJUSTABLE MATTRESS BASE IS A FREESTANDING MATTRESS SUPPORT THAT SITS WITHIN THE PERIMETER OF THE BED FRAME.

IF USING THIS BED FRAME WITH A STANDARD BOX SPRING OR FOUNDATION THESE INSTRUCTIONS DO NOT APPLY.

PRE-ASSEMBLED SIDE RAIL CLEATS OBSTRUCT ADJUSTABLE BASE INSTALLATION AND OPERATION. FOLLOW THESE INSTRUCTIONS TO REMOVE THEM.



WARNING!


SIDE RAIL CLEATS ARE HELD IN PLACE USING PHILLIPS HEAD SCREWS. ONCE THEY ARE REMOVED THE USER WILL NOT BE ABLE TO SAFELY RE-INSTALL THE SIDE RAIL CLEATS FOR FUTURE USE WITH A STANDARD BOX SPRING OR FOUNDATION.

THE FOLLOWING PARTS ARE NOT REQUIRED FOR ADJUSTABLE MATTRESS BASE INSTALLATION:

D. SLAT	26 PCS
E. CENTER SLAT SUPPORT	1 PC
F. SIDE RAIL SLAT CLIP	26 PCS
G. CENTER SUPPORT SLAT CLIP	13 PCS
H. SLAT SUPPORT LEG	2PCS

STEP 1:

USE A PHILLIPS HEAD SCREWDRIVER (NOT PROVIDED) AND ALLEN KEY (6) TO UNSCREW THE PHILLIPS SCREWS AND ALLEN BOLTS IN ORDER TO REMOVE THE PRE-ASSEMBLED SIDE RAIL CLEATS.



UPDATED:APRIL 26TH, 2023