

## PREMIUM PLUS POLYPROPYLENE FILM PACKAGING TAPE

### TYPICAL APPLICATIONS

- To seal, repair and bundle corrugated cartons and paper or film containers in a broad temperature range

### ADVANTAGES AND BENEFITS

- Excellent initial tack
- High holding power
- Usable in wide temperature range
- Available in short or long length rolls for use with hand held or machine dispensers


### CONSTRUCTION

Overall Grade/Function: Premium Plus  
Backing: Biaxially oriented polypropylene film (BOPP)  
Adhesive: High tack, solvent based acrylic

### COLOR(S)



Clear (CLR)



### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

914 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	25 oz/in width	2.74 N/10 mm
Thickness	2 mils	0.05 mm
Elongation	140%	140%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

CID A-A-1684C

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PP-802-08/14/2014