

# Jones Stephens' PlumBite® Push to Connect Repair Couplings

## **Specifications**

Jones Stephens' PlumBite® Push to Connect Repair Couplimgs are a heat-free method of joining Copper and/or CPVC tubing, designed to save time on installation and to connect piping with relative ease and confidence. No soldering, glue, heat or external tools are required to join the pipe. Just insert the pipe and the stainless steel gripper ring, bite down, and hold the pipe tightly while the EPDM o-ring seals against leakage. Disassembly is just as fast using the optional disassembly tool, so fittings can be easily removed and re-used.

### **Applications**

Jones Stephens' PlumBite® Push to Connect Repair Couplings are approved for use with commercial and residential potable and non-potable water applications.

#### **Materials**

Body-DZR Brass O-Ring- EPDM, Peroxide Cured Gripper Ring- Stainless Steel

## **Dimensions and Product Offering**

PART NO. INDIVIDUAL	PART NO. BULK	A NOMINAL (IN.)	B (IN.)	B TOLERANCE +/- (IN.)
C77470LF*	C76530LF	0.50	4.45	0.08
C77471LF*	C76531LF	0.75	4.47	0.08
C77472LF*	C76532LF	1.00	4.34	0.08

#### **Performance Specifications**

- Maximum Temperature 180 degrees F
- Maximum Pressure 200 PSI

#### **Certifications/Listings/Approvals**

NSF/ANSI/CAN 61

NSF/ANSI/CAN 372

NSF/ANSI 14

**ASSE 1061** 

**SDWA Compliant** 


Lead Law Compliant

MASS Approved


Vermont Act 193 Compliant



800.355.6637 jonesstephens.com









\* Tool included to assist installation