



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 07-2645-5 | Version Number: | 22.02 |
| Issue Date: | 01/14/19 | Supersedes Date: | 02/16/18 |

SECTION 1: Identification

1.1. Product identifier

3M™ STAMARK™ Surface Preparation Adhesive P-50

Product Identification Numbers

| ID Number | UPC | ID Number | UPC |
|----------------|------------------|----------------|------------------|
| 41-3400-0267-8 | | 75-0300-1882-6 | 00-51138-38540-8 |
| 75-0300-2558-1 | 00-51138-57141-2 | 75-0300-6906-8 | 00-51138-73609-5 |

4010030614, 7000004817, 7000004818

1.2. Recommended use and restrictions on use

Recommended use

Pavement marking tape adhesive, Pavement marking adhesive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Transportation Safety Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 2.
 Serious Eye Damage/Irritation: Category 2A.
 Reproductive Toxicity: Category 1B.
 Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---------------|------------|------------------------|
| Ethyl acetate | 141-78-6 | 30 - 60 Trade Secret * |

| | | |
|---|-------------|--------------------------|
| Methyl ethyl ketone | 78-93-3 | 30 - 60 Trade Secret * |
| Heptane, branched, cyclic and linear | 426260-76-6 | 7 - 13 Trade Secret * |
| Naphtha, light steam-cracked arom, piperylene conc., polymd. | 68478-07-9 | 7 - 13 Trade Secret * |
| Styrene - isoprene copolymer | 25038-32-8 | 5 - 10 |
| Hydrotreated heavy naphthenic petroleum distillates | 64742-52-5 | 0.5 - 1.5 Trade Secret * |
| Terpenes and Terpenoids, turpentine-oil, .alpha.-pinene fraction, polymd. | 70750-57-1 | 0.5 - 1.5 Trade Secret * |
| Toluene | 108-88-3 | < 0.3 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes
Hydrocarbons
Methane
Carbon monoxide
Carbon dioxide
Ketones
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|------------|--------|--------------------------|--------------------------------|
| Toluene | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human carcin |
| Toluene | 108-88-3 | OSHA | TWA:200 ppm;CEIL:300 ppm | |
| Ethyl acetate | 141-78-6 | ACGIH | TWA:400 ppm | |
| Ethyl acetate | 141-78-6 | OSHA | TWA:1400 mg/m3(400 ppm) | |
| Paraffin oil | 64742-52-5 | OSHA | TWA(as mist):5 mg/m3 | |
| PETROLEUM DISTILLATES | 64742-52-5 | OSHA | TWA:2000 mg/m3(500 ppm) | |
| Methyl ethyl ketone | 78-93-3 | ACGIH | TWA:200 ppm;STEL:300 ppm | |
| Methyl ethyl ketone | 78-93-3 | OSHA | TWA:590 mg/m3(200 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:

Liquid

Odor, Color, Grade:

Pale yellow, solvent odor

| | |
|---|---|
| Odor threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>Not Applicable</i> |
| Boiling Point | >=170 °F |
| Flash Point | 15 °F [<i>Test Method</i> :Tagliabue Closed Cup] |
| Evaporation rate | >=4.3 [<i>Ref Std</i> :BUOAC=1] |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | 1.2 % |
| Flammable Limits(UEL) | 11 % |
| Vapor Pressure | <=76 mmHg [<i>@</i> 68 °F] |
| Vapor Density | 2.4 - 3.5 [<i>Ref Std</i> :AIR=1] |
| Density | 0.68 - 0.9 g/ml [<i>@</i> 20 °C] |
| Specific Gravity | .68 - 0.9 [<i>Ref Std</i> :WATER=1] |
| Solubility in Water | Slight (less than 10%) |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 50 centipoise |
| Molecular weight | <i>No Data Available</i> |
| Volatile Organic Compounds | 745 - 755 g/l |
| Percent volatile | 75 - 85 % weight |
| VOC Less H2O & Exempt Solvents | <i>Not Applicable</i> |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong acids

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be

present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|----------------------------|---------|--|
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Methyl ethyl ketone | Dermal | Rabbit | LD50 > 8,050 mg/kg |
| Methyl ethyl ketone | Inhalation-Vapor (4 hours) | Rat | LC50 34.5 mg/l |
| Methyl ethyl ketone | Ingestion | Rat | LD50 2,737 mg/kg |
| Ethyl acetate | Dermal | Rabbit | LD50 > 18,000 mg/kg |
| Ethyl acetate | Inhalation-Vapor (4 hours) | Rat | LC50 70.5 mg/l |
| Ethyl acetate | Ingestion | Rat | LD50 5,620 mg/kg |
| Naphtha, light steam-cracked arom, piperylene conc., polymd. | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| Naphtha, light steam-cracked arom, piperylene conc., polymd. | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Heptane, branched, cyclic and linear | Dermal | Rabbit | LD50 > 2,000 mg/kg |

| | | | |
|---|----------------------------|---------------|--------------------|
| Heptane, branched, cyclic and linear | Inhalation-Vapor (4 hours) | Rat | LC50 > 73.5 mg/l |
| Heptane, branched, cyclic and linear | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Styrene - isoprene copolymer | Dermal | Not available | LD50 > 2,000 mg/kg |
| Styrene - isoprene copolymer | Ingestion | Not available | LD50 > 2,000 mg/kg |
| Hydrotreated heavy naphthenic petroleum distillates | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Hydrotreated heavy naphthenic petroleum distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Toluene | Dermal | Rat | LD50 12,000 mg/kg |
| Toluene | Inhalation-Vapor (4 hours) | Rat | LC50 30 mg/l |
| Toluene | Ingestion | Rat | LD50 5,550 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-----------------------|---------------------------|
| Methyl ethyl ketone | Rabbit | Minimal irritation |
| Ethyl acetate | Rabbit | Minimal irritation |
| Naphtha, light steam-cracked arom, piperylene conc., polymd. | similar compounds | No significant irritation |
| Heptane, branched, cyclic and linear | Rabbit | Mild irritant |
| Styrene - isoprene copolymer | Professional judgment | No significant irritation |
| Hydrotreated heavy naphthenic petroleum distillates | Rabbit | Minimal irritation |
| Toluene | Rabbit | Irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-----------------------|---------------------------|
| Methyl ethyl ketone | Rabbit | Severe irritant |
| Ethyl acetate | Rabbit | Mild irritant |
| Naphtha, light steam-cracked arom, piperylene conc., polymd. | similar compounds | Mild irritant |
| Heptane, branched, cyclic and linear | Rabbit | Mild irritant |
| Styrene - isoprene copolymer | Professional judgment | No significant irritation |
| Hydrotreated heavy naphthenic petroleum distillates | Rabbit | Mild irritant |
| Toluene | Rabbit | Moderate irritant |

Skin Sensitization

| Name | Species | Value |
|---|------------|----------------|
| Ethyl acetate | Guinea pig | Not classified |
| Styrene - isoprene copolymer | | Not classified |
| Hydrotreated heavy naphthenic petroleum distillates | Guinea pig | Not classified |
| Toluene | Guinea pig | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---------------------|----------|---------------|
| Methyl ethyl ketone | In Vitro | Not mutagenic |
| Ethyl acetate | In Vitro | Not mutagenic |
| Ethyl acetate | In vivo | Not mutagenic |
| Toluene | In Vitro | Not mutagenic |
| Toluene | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|------------|---------|--|
| Methyl ethyl ketone | Inhalation | Human | Not carcinogenic |
| Hydrotreated heavy naphthenic petroleum distillates | Ingestion | Rat | Not carcinogenic |
| Hydrotreated heavy naphthenic petroleum distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---------------------|------------|--|---------|---------------------|------------------------|
| Methyl ethyl ketone | Inhalation | Not classified for development | Rat | LOAEL 8.8 mg/l | during gestation |
| Toluene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| Toluene | Ingestion | Toxic to development | Rat | LOAEL 520 mg/kg/day | during gestation |
| Toluene | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------------|------------|-----------------------------------|--|-------------------------|---------------------|-------------------|
| Methyl ethyl ketone | Inhalation | central nervous system depression | May cause drowsiness or dizziness | official classification | NOAEL Not available | |
| Methyl ethyl ketone | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Methyl ethyl ketone | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| Methyl ethyl ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | not applicable |
| Methyl ethyl ketone | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 1,080 mg/kg | not applicable |
| Ethyl acetate | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethyl acetate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Ethyl acetate | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Heptane, branched, cyclic | Inhalation | central nervous | May cause drowsiness or | Human | NOAEL not | |

| | | | | | | |
|---|------------|-----------------------------------|--|-------|---------------------|------------------------|
| and linear | | system depression | dizziness | | available | |
| Hydrotreated heavy naphthenic petroleum distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Toluene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| Toluene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------|------------|--|--|-------------------------|-----------------------|------------------------|
| Methyl ethyl ketone | Dermal | nervous system | Not classified | Guinea pig | NOAEL Not available | 31 weeks |
| Methyl ethyl ketone | Inhalation | liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles | Not classified | Rat | NOAEL 14.7 mg/l | 90 days |
| Methyl ethyl ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | 7 days |
| Methyl ethyl ketone | Ingestion | nervous system | Not classified | Rat | NOAEL 173 mg/kg/day | 90 days |
| Ethyl acetate | Inhalation | endocrine system liver nervous system | Not classified | Rat | NOAEL 0.043 mg/l | 90 days |
| Ethyl acetate | Inhalation | hematopoietic system | Not classified | Rabbit | LOAEL 16 mg/l | 40 days |
| Ethyl acetate | Ingestion | hematopoietic system liver kidney and/or bladder | Not classified | Rat | NOAEL 3,600 mg/kg/day | 90 days |
| Toluene | Inhalation | auditory system nervous system eyes olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| Toluene | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| Toluene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| Toluene | Inhalation | hematopoietic system vascular system | Not classified | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 625 mg/kg/day | 13 weeks |
| Toluene | Ingestion | heart | Not classified | Rat | NOAEL 2,500 | 13 weeks |

| | | | | | mg/kg/day | |
|---------|-----------|-------------------------------|----------------|-------------------------|-----------------------|----------|
| Toluene | Ingestion | liver kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| Toluene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |
| Toluene | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |

Aspiration Hazard

| Name | Value |
|--------------------------------------|-------------------|
| Heptane, branched, cyclic and linear | Aspiration hazard |
| Toluene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Reproductive toxicity
 Serious eye damage or eye irritation
 Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 07-2645-5 | Version Number: | 22.02 |
| Issue Date: | 01/14/19 | Supersedes Date: | 02/16/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com