



Product Change Notice: 3M™ Round, Shielded/Jacketed, Flat Cable Series 3659, .050” 28 AWG Stranded, PVC

Issue Number: 540

Date: May 31, 2004

To: 3M Electronic Solutions Division Global Copy List
3M Electronic Solutions Division Distribution List
3M Electronic Solutions Manufacturing Rep Firm List
Mara Guzman, 3M EMD

Product Change

Product: All Versions TS-0083

3659/09(300')	80610801922
3659/10(300')	80610801963
3659/14(300')	80610802003
3659/15(300')	80610802045
3659/16(300')	80610802086
3659/20(300')	80610802128
3659/24(300')	80610802169
3659/25(300')	80610811251
3659/26(300')	80610802243
3659/34(300')	80610802284
3659/36(300')	80610802326
3659/37(300')	80610802367
3659/40(300')	80610802409
3659/50(300')	80610802441
3659/60(300')	80610802482
3659/64(300')	80610802524

Enhancement:

3M ESD is pleased to announce 3M Round, Shielded/Jacketed, Flat Cable Series 3659 is now RoHS Compliant.

3M's intent is to offer products that allow our customers to be in compliance with European Union directive 2002/95/EC (Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment). 3M's determination of compliance is based on the current RoHS legislation and certification from 3M raw material suppliers. This change does not affect the form, fit or function of the cable, therefore product numbers and stock numbers will remain unchanged. The description, as well as the factory run number, will be updated to include "RC" for RoHS Compliant.

The 3M™ Round Conductor Flat Cable Series 3659 is available in standard lengths of 300 feet with a minimum order quantity of one roll.

No new literature will be issued at this time. Please use the latest revision of TS-0083 which lists the RoHS and WEEE compliance in the Features and Benefits section.

Actions Required:

- Please notify customers of this enhancement.

Thank you for your continued support of 3M products.

Please direct all correspondence on this matter to:

*Jeff Bullion
Copper Product Marketing
Phone: 512-984-5982
Email: jbullion@mmm.com*

3M is a trademark of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**



Electronic Solutions Division
6801 River Place Blvd.
Austin, TX 78726-9000
www.3M.com/interconnects