# **Cyber Power**

### CP425G

The CP425G UPS system offers significant energy savings, battery backup and surge protection for home/office computers and connected electronics.



#### **KEY FEATURES:**

- 425VA / 255W Simulated sine wave
- Standby Topology
- GreenPower UPS™
- Compact Desktop Form Factor
- RJ11 Protection (1-in, 2-out)
- 8 Outlets
- EMI/RFI filters

Runtimes: 2 Minutes at Full-load 7 Minutes at Half-load

#### **DESIGNED FOR:**

- Workstations/PCs
- Home Office/Small Office
- Personal Electronics
- POS Terminals

The CyberPower Standby CP425G uninterruptible power supply (UPS) safeguards a home office PC and other electronics (monitors, printers, scanners, speakers, fax machines, CD/DVD players and iPods) from surges, spikes, sags, brownouts and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection. Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.

The CP425G unit has a capacity of 425VA/255Watts, eight (8) NEMA 5-15R receptacles, widely-spaced to accommodate transformer-based plugs. Its compact design allows for horizontal or vertical placement, or it can be conveniently mounted on a wall. This UPS has a maintenance-free, 12V/3Ah battery. Protection for phone/network (RJ11) is also included. EMI/RFI filters increase the immunity of the load to disturbances and surges.

### **FEATURES & BENEFITS:**

Energy-Saving Technology: Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.

**Ultra-Quiet Operation:** Lowest sound emissions of any UPS in its class.

**EMI/RFI Filters:** Filters against electromagnetic interference and radio frequency interference ensuring clean power for connected equipment.

**Transformer-Spaced Outlets:** Widely-spaced outlets accommodate large transformer-based plugs without compromising the utility of other outlets.

**Convenient Mounting:** Compact size for mounting horizontal or vertical.

 $\ensuremath{\textbf{LED}}$  Indicators: LED status lights indicate Power-On and wiring faults.

**Audible Alarms:** Distinctive tones identify when the unit is running on battery power, if it is overloaded or when the battery is low.

Resettable Circuit Breaker: Convenient unit reset switch in case of an overload.

**Technical Support:** CyberPower assists users with any product, installation, or warranty concerns – free of charge.

**3-Year Warranty:** Stringent manufacturing processes and innovative product design enables CyberPower to offer one of the strongest warranties in our industry. CyberPower will repair or replace damaged units within three (3) years of purchase date.

ISO & Safety Certifications: All CyberPower manufacturing facilities are state-of-the-art and ISO-9001 Quality Tested. Our products are certified by the FCC, cUL, and UL.



CyberPower's patented GreenPower UPS™ technology reduces UPS energy costs up to 75%! Save money and help reduce carbon emissions.

CyberPower Systems, Inc. 4241 12th Ave. E. Suite 400 Shakopee, MN 55379 Toll-free 877.297.6937 CPSww.com

# **Cyber Power**

GENERAL	
JPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
NPUT	Green energy 2 rings Emererally
/oltage	96Vac - 140Vac
Frequency	47Hz - 63Hz
Plug Type	NEMA 5-15P
Plug Style	Right angle, 45-degree, offset right
Cord Length	6'
OUTPUT	105
/A	425
Watts	255
On Battery Voltage	120Vac +/- 5%
On Battery Frequency	50/60Hz +/5%
On Battery Waveform	Simulated Sine Wave
Outlets-Total	8
Dutlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4
BATTERY	
Runtime at Half Load (min.)	7
Runtime at Full Load (min.)	2
Battery Type	Sealed lead acid
Battery Size	12V/3AH
User Replaceable	No
Typical Recharge Time	8 Hours
Replacement Battery	BB Battery - BP3-12
Battery Quantity	1
SURGE PROTECTION AND FILTERING	
Surge Suppression	890 Joules
Phone Protection RJ11	1-ln, 2-Out
EMI/RFI Filtration	Yes
MANAGEMENT & COMMUNICATIONS	N.
HID Compliant USB Port	No
Serial Port	No
Management Cable	None
ED Indicators	Power on, wiring fault
Audible Alarms	On battery, low battery, overload
Software	None
PHYSICAL	
Dimensions (WxHxD)	9.75" x 6" x 3"
Veight (lbs.)	5
Keyhole Mounting Slots	Yes
CERTIFICATIONS	
Certifications	UL1449, cUL, FCC DOC Class B
RoHS Compliant	Yes
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
Joinnous Equipment duarantes	2001110





CyberPower Systems, Inc. designs and manufactures state-of-the-art power protection and distribution equipment for corporate, business, home, government and educational markets. CyberPower leads the industry by surpassing customer expectations in the development, design, construction, durability and functionality of uninterruptible power supply (IJPS) products for computers, peripherals and connected devices. CyberPower Systems operates in the Asian Pacific, North American, and European markets. For additional information, including sales office locations and authorized reseller partners, visit CPSww.com.

© 2011 CyberPower Systems (USA), Inc. All rights reserved. All other trademarks are the property of their respective owners. CyberPower reserves the right to modify product information or specifications without previous notice. The information presented is accurate at the time of publication. 11-2011