

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings LCP, LC6, L7XP, L7XPR, L7X and L7XR.

CONSTRUCTION

Durable powder-coated steel finishing trim.

Steel yoke allows for socket attachment to attain positive lamp positioning.

INSTALLATION

Socket to trim interface.

Trim retention is achieved by utilizing two side-mounted torsion springs on the trim and two receiving brackets in the can, ensuring a consistently tight fit with the ceiling.

LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

WARRANTY

1-year limited warranty. Complete warranty terms located at

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

6" Finishing Trim

7X1

OPEN SHALLOW


Wide Flange

Economy




Specifications	
Height:	3-7/8 (9.8) – 7X1MW 4-1/4 (10.8) – 7XB1MW
Lamp opening:	4-1/4 (10.8)
Diameter:	7-3/4 (19.7)

All dimensions are inches (centimeters) unless otherwise indicated.



7X1MW



7XB1MW

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 7XB1MW TOR

Series	TOR		Packaging
	Mounting method		
7X1MW	Matte white open top	TOR Torsion springs	R6 Resale pack of six
7XB1MW	Matte white baffle open top		U Unit

Housing Compatibility: Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	75 PAR30 (short neck)	LCP, LC6, L7XP, L7XPR, L7X, L7XR
		65 BR30	LCP, LC6, L7XP, L7XPR, L7X, L7XR

