



MP1058SSW MULTI-PACK SOLUTION

Power, surge protection and USB charging solutions for home and office electronics

The Cyberpower MP1058SSW multi-pack comes with one eight-outlet surge protector strip with USB-A and USB-C, one seven-outlet surge protector strip with USB-A, and one six-outlet wall-tap surge protector with USB-A and USB-C.

The eight-outlet surge protector in this multi-pack provides 2700 joules of protection to prevent damaging power spikes and surges from reaching your electronics. It features two USB ports (one 2.4A USB-A port and one 20W USB-C port with Power Delivery) that will charge USB-enabled mobile devices and small electronics. The P806UCPD has a six-foot power cord, a low-profile plug that fits in tight spaces, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.

The six-outlet surge protector wall-tap in this multi-pack provides 2000 joules of protection to prevent damaging power spikes and surges from reaching your electronics. It features two USB ports (one 2.4A USB-A port and one 20W USB-C port with Power Delivery) that will charge USB-enabled mobile devices and small electronics. The P6WSUCPD has swiveling outlets that rotate 90 degrees to help with cord management, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.

The seven-outlet surge protector in this multi-pack provides 2000 joules of protection to prevent damaging power spikes and surges from reaching your electronics. It features two USB-A ports with 2.4A shared output that will charge USB-enabled mobile devices and small electronics. The P704URC1 has a four-foot power cord, a low-profile plug that fits in tight spaces, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.



TYPICAL APPLICATIONS

- Consumer Electronics
- Personal Computers
- Chargers

FEATURES - P6WSUCPD | 6-OUTLET WALL-TAP

- AC outlets: 6
- Outlet type: NEMA 5-15R
- Surge suppression: 2000J
- USB-A ports: 1
- USB-A output: 2.4A
- USB-C ports: 1
- USB-C output: 20W PD
- Plug type: NEMA 5-15P
- Warranty: One-Year Limited

FEATURES - P704URC1 | 8-OUTLET POWER STRIP

- AC outlets: 8
- Outlet type: NEMA 5-15R
- Surge suppression: 2700J
- USB-A ports: 1
- USB-A output: 2.4A
- USB-C ports: 1
- USB-C output: 20W PD
- Plug type: NEMA 5-15P
- Plug style: Right-angle 45° offset
- Power cord length: 6 ft.
- Warranty: One-Year Limited

FEATURES - P806UCPD | 7-OUTLET POWER STRIP

- AC outlets: 7
- Outlet type: NEMA 5-15R
- Surge suppression: 2000J
- USB-A ports: 2
- USB-A output: 2.4A (shared)
- Plug type: NEMA 5-15P
- Plug style: Right-angle 45° offset
- Power cord length: 4 ft.
- Warranty: One-Year Limited

MP1058SSW

MULTI-PACK SOLUTION

SPECIFICATIONS

	P6WSUCPD	P704URC1	P806UCPD
INPUT			
Voltage	125V		
Plug Type	NEMA 5-15P		
Plug Style	Three Prong Direct Plug-in	Right Angle, 45° Offset Right	Right Angle, 45° Offset Right
Cord Length	Wall-tap	4 ft	6 ft
OUTPUT			
Outlet Type	NEMA 5-15R		
Outlets - Total	6	7	8
Outlets - Widely-spaced	0	1	2
Output Voltage	125V		
USB Charge Ports	1 USB-A, 1 USB-C	2 USB-A	1 USB-A, 1 USB-C
USB-A Charge Port Output	2.4A	2.4A (shared)	2.4A
USB-C Charge Port Output	20W PD (5V, 9V)	N/A	20W PD (5V, 9V)
SURGE PROTECTION & FILTERING			
Attenuation	32 dB		
Surge Suppression	2000J	2000J	2700J
Clamping Voltage	600V (L-N L-G N-G)		
Response Time	< 1 Nanosecond		
EMI/RFI Filtration	150KHz to 100MHZ		
Auto Shutdown (Safe Fail)	Yes		
INDICATORS			
LED Indicators	Protected(Green)		
	Grounded(Green)		
PHYSICAL			
Color	White		
Keyhole Mounting Slots	No	Yes	No

	P6WSUCPD	P704URC1	P806UCPD
DIMENSIONS			
Physical Dimensions - Width/Height/Depth (cm)	10.3 x 16.3 x 3.51 cm	5.2 x 4.1 x 32 cm	10.1 x 3.4 x 20.2 cm
Physical Dimensions - Width/Height/Depth (mm)	103 x 162.6 x 35.1 mm	52 x 41 x 320 mm	100.7 x 34 x 201.8 mm
Physical Dimensions - Width/Height/Depth (in.)	4.06 x 6.4 x 1.38 in.	2.05 x 1.61 x 12.6 in.	3.96 x 1.34 x 7.94 in.
SHIPPING DIMENSIONS			
Shipping Dimensions - Width/Height/Depth (cm)	36.5 x 40.49 x 5.69 cm		
Shipping Dimensions - Width/Height/Depth (mm)	365 x 404.9 x 56.9 mm		
Shipping Dimensions - Width/Height/Depth (in)	14.37 x 15.94 x 2.24 in.		
Weight (kg)	6.84 kg		
Weight (lb)	15.09 lbs.		
CERTIFICATIONS			
Environmental	RoHS Compliant		
Safety	UL498A, 1449, 1310, cUL	UL1363, 1449, 1310, cUL	UL1363, 1449, 1310, cUL
WARRANTY			
Product Warranty	One-Year Limited Warranty		
Connected Equipment Guarantee	Yes		
CEG Amount	\$100,000	\$200,000	