## **INSTALLATION IS**

## 46001/46002/46003/46004 INSTALLATION INSTRUCTIONS

INSTALLATION IS NOW COMPLETED

Please read carefully and save these instructions as you may need them a later date.

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

All electrical connections must be in accordance with local and National Electrical Cod (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts ar missing by referencing the illustration.

## ASSEMBLY AND INSTALLATION

- 1. Carefully unpack the fixture, lay out all parts on a clean surface.
- 2. Mount the mounting bracket (2) to the outlet box (1) by using two outlet box screws (4).
- 3. Tie the ground wires (7&5) from fixture and from outlet box to the ground screw (6) on the mounting bracket (2). Connect the white fixture wire (11) from the fixture to the white wire (neutral wire 12) from the supply circuit. Connect the black fixture wire (9) from the fixture to the black wire (live wire 10) from the supply circuit.
- 4. Cover the connections by using provided wire connectors (8). Position wires back inside the outlet box (1).
- 5. Place the back plate (13) onto the mounting screw(3), and secure it into place using the decorative nuts (14) provided
- 6.Install the bulb (15 not included) into the socket. Make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label.
- 7.Slide the glass shade (16) over the socket, turn glass shade(16) clock wise until it will no longer turn.
- 8. Turn on the power.

