



P600WUHD

6-OUTLET WALL-TAP WITH USB

Wall-tap surge protector with USB charging

The P600WUHD Wall-tap Surge Protector with USB safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 500 joules of protection, has six surge-protected outlets and a wall-tap plug. Two USB ports (3.4 Amp shared) charge mobile, USB enabled devices. The P600WUHD also features EMI/RFI noise filtering, an impact-resistant casing, and an integrated device shelf on top of the unit for convenient charging and cord management.

The P600WUHD also features metal oxide varistor (MOV) technology, an EMI/RFI noise filter, and impact-resistant casing. This surge protector wall-tap comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 500 J
- Volts: 125 V
- Circuit breaker: 15A
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB charge ports: 2
- USB charge output: 3.4A (shared)
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$25,000



SPECIFICATIONS

INPUT	
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	6 x NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	3.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

P600WUHD

6-OUTLET WALL-TAP WITH USB

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
PHYSICAL	
Color	White
Form Factor	Wall-tap
Form Factors Supported	Direct plug
Material of Construction	Plastic

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	3.49 x 17.46 x 10.16 cm
Physical Dimensions - Width/Height/Depth (mm)	35 x 175 x 102 mm
Physical Dimensions - Width/Height/Depth (in.)	1.375 x 6.875 x 4 in.
Weight (kg)	0.27 kg
Weight (lb)	0.60 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	10.16 x 17.46 x 6.03 cm
Shipping Dimensions - Width/Height/Depth (mm)	101.6 x 174.63 x 60.33 mm
Shipping Dimensions - Width/Height/Depth (in.)	4 x 6.875 x 2.375 in.
Shipping Weight (kg)	0.28 kg
Shipping Weight (lbs.)	0.61 lbs.
CERTIFICATIONS	
Safety	UL1449 3rd Edition
Environmental	RoHS Compliant
WARRANTY	
CEG Amount	\$15,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited