For Commercial, Residential & Institutional HVAC Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

LEAD FREE*

Series LFDPG-5Top Entry Pressure Gauges

Dial Sizes: 2"

LFDPG-5 Top-Entry Pressure Gauges are used in commercial, residential, and institutional HVAC applications. The LFDPG-5 features Lead Free* construction to comply with Lead Free* installations requirements. These gauges feature ABS polymer cases, Kostil Polymer windows, \$\frac{1}{8}\text{"} or \$\frac{1}{4}\text{"} NPT connections, and copper alloy Bourdon tube sensing elements. Accuracy is ASME, Type B. Series LFDPG-5 gauges are available in various pressure rating scales. The dual scale features PSI and kPa measurements.

Features

- ABS polymer case
- Kostil polymer window
- Copper alloy Bourdon sensing element
- Tin alloy welding
- 1/8" or 1/4" Lead Free Brass NPT connections
- ASME Type "B" accuracy

Standards

ASME B40.100 EN ISO 9001:2008 EN ISO 14001:2004

Temperature

Working Temperature: -4°F to 176°F (-20°C to 80°C)

Materials

Case: ABS polymer Window: Kostil polymer

Sensing Element: Copper alloy Bourdon tube

Welding: Tin alloy

Connector: Lead Free Brass



LFDPG-5

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.


NOTICE

Inquire with governing authorities for local installation requirements

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



Dimensions – Weights



MODEL	SCAL	LE	SIZE	DIMENSIONS						WEIGHT	
					A B		С				
			in.	in.	mm	in.	mm	in.	mm	lbs.	kgs
DPG5-2	0 – 160psi	1103 kPa	1/8	2	50	211/16	68	11/16	27	.15	.07
DPG5-2	0 – 160psi	1103 kPa	1/4	2	50	213/16	71	11/16	27	.2	.09



USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca Latin America: T: (52) 81-1001-8600 • Watts.com

ES-LFDPG-5 1526 © 2015 Watts