

PRODUCTION GRADE POLY COATED DUCT TAPE



DESCRIPTION

This tape is made of a Polyester (PET) cloth / Polyethylene (PE) film with rubber adhesive combined to provide a quality utility product. Conformable to irregular surfaces.

MAIN FEATURES

- High shear, high tack natural rubber adhesive.
- Strong holding power provides excellent bond.
- Very conformable.
- Water and moisture resistant.

APPLICATIONS

- Wrapping & sealing, binding & bundling.
- General light maintenance.

TECHNICAL DATA

Color.....	Silver (21)
Backing.....	Polyethylene film laminated to polyester scrim
Adhesive.....	High tack natural rubber adhesive
Thickness.....	6.5 mil
Adhesion to steel.....	55 oz/in
Tensile strength (machine direction).....	19 lb/in
Elongation.....	17%
Temperature Resistance.....	Up to 50°C (122 °F)

HIGH TACK ADHESIVE

STRONG HOLDING POWER

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.