

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

Cuts hard-to-reach branches from aerial basket or from the ground. Super Spool selector control for use on Open- and Closed-Center hydraulic systems. Available in three lengths. Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269

PRODUCT NAME –

Page Title

HTMA Female Coupler - 9/16 - 18 SAE O-Ring External Thread

PRODUCT OVERVIEW –

Marketing Text 1

Cuts hard-to-reach branches from aerial basket or from the ground

Marketing Text 2

Super Spool selector control for use on Open- and Closed-Center hydraulic systems

Marketing Text 3

Available in three lengths

Marketing Text 4

Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269

Marketing Text 5

Safety features include: two-step trigger, trigger guard, and fully covered sprocket guard

Marketing Text 6

Anti-kickback chain and automatic chain oiler

Marketing Text 7

Rugged high torque gear motor

Marketing Text 8

Unfilled and foam-filled extension tube versions offered

PRODUCT SPECIFICATION –

Product Specification 1

Connection : 9/16-18 SAE O-Ring External Thread

Product Specification 2

Operating Pressure : 3000 PSI (207 BAR)

Product Specification 3

Type : HTMA Female, Hydraulic